

Specifications:

- Frequency range: (up to 450MHz on 3rd harmonics)
 - A: 100KHz ~ 320KHz
 - B: 300KHz ~ 1,100KHz
 - C: 1MHz ~ 3.3MHz
 - D: 3.0MHz ~ 11MHz
 - E: 10MHz ~ 35MHz
 - F: 32MHz ~ 150MHz
- Frequency accuracy: $\pm 5\%$.
- RF output: 100mVrms, approx (up to 35MHz unloaded).
- Output control: HIGH-LOW switch and fine adjuster.
- Modulation:
 - INT. 1KHz (AM) 30% approx.
 - EXT. 50Hz ~ 20KHz, at less than 1Vrms input.
- Audio output: 1KHz, Min. 2 Vrms.
- Crystal oscillator: For 1 ~ 15MHz crystal in type HC-6u holder (not included).
- Power requirement: AC 115 / 230V, 50 / 60Hz Approx 3VA.
- Dimensions & weight:
 - 150 (H) x 250 (W) x 130 (D) mm.
 - Approx 2.5kgs.
- Accessories: BNC-clips x 1.

Features:

- Wide frequency range: 100KHz ~ 150MHz.
- With 1KHz oscillator in inner part for the purpose of modulation.
- Of portable type, high stability.