

FinishPro™ 25XP XtremePro 18 Gauge Brad Nailer



The Senco FinishPro™ 25XP has redefined the brad nailer category! This lightweight, power-packed nailer is loaded with all the features you need, plus a few more. The FinishPro™ 25XP drives both slight and medium headed 18 ga. brads from 5/8" to 2-1/8" into the hardest woods. The "on-tool" power adjustment allows the user to increase power by 30%. All this, plus Senco's exclusive NeverLube® design to keep your work surface oil free.

Applications:

Molding and decorative trim, furniture trim, window beading, blind pinning of upholstered and trim panels, rattan, scribe molding, cabinets, drawers and picture frame assembly

Features and Benefits:


- Two-year warranty
- **NEW!** Comfort and convenient features include: overmold comfort grip, overmold trigger, "on-tool" power adjustment, 360° adjustable exhaust, and belt hook
- Lightweight at 2.7 lbs for easy maneuvering and all day work
- Drives slight and medium head 18 gauge brads from 5/8" (15mm) to 2-1/8" (55mm)
- On-tool power adjustment to lengthen the life of the tool when used primarily with shorter fasteners
- Wrenches onboard to make the adjustment fast and easy
- NeverLube technology – no lubrication required

Tool Specifications:

Weight: 2.7 lbs (1.227 kg)
 Height: 9.9" (251.46 mm)
 Length: 10" (254 mm)
 Width: 2.2" (55.88 mm)
 Nail Capacity: 110
 Operating Pressure: 70-120 psig
 Mode of Operation: Restrictive Trigger only

Fastener Specifications:

The FinishPro™ 25XP drives both slight headed and medium headed 18 gauge brads from 5/8" to 2-1/8".



Power Adjustment:

The FinishPro™ 25XP has the unique ability to increase or decrease the power output with a simple adjustment located on the tool. The Standard setting for the FinishPro™ 25XP allows you to accomplish most jobs. **This is the factory setting.** The Turbo setting on the FinishPro™ 25XP gives you a 30% increase in power for longer brads and harder wood applications. For complete details on how to operate the power adjustment, please refer to the operators manual.

Standard Setting



Turbo Setting





HARD WORK. BRING IT ON.™

FinishPro™ 25XP XtremePro 18 Gauge Brad Nailer

Adjustable Exhaust
No tools required

Comfort Overmold Grip
Reduces vibration and fatigue

Angled Air Inlet
Keeps the hose off the work surface when the tool is in the vertical position

On-tool Power Adjustment
Lengthens the life of the tool by allowing the user to choose the right power setting for the job. Wrenches provided onboard to make the adjustment fast and easy

Lightweight & Maneuverable
At only 2.7 lbs, for easy maneuvering and light enough for all day work

Overmold Trigger

SENCO Exclusive NeverLube® Design
Keeps the work surface free of oil

Variable Thumbwheel Adjustable Depth-of-Drive
Allows user to achieve the right depth of countersink

Last Brad Lock Out
Lengthens the life of the tool

No-Mar Pad & Square Nose Safety
Protects work surface and the square nose safety design keeps the tool from slipping out of position

* "Restrictive Trigger" activated tools are used for applications where precision nail or staple placement is desired. You must first depress the safety element where you want to drive a nail or staple and then pull the trigger. After each nail or staple is driven, completely release the trigger and lift the tool off the work surface.

For instructions on safe use of tools, please refer to the Operating Instructions or Customer Satisfaction and Safety Reminder contained in your tool carton.