GU GEARWRENCH

CV Boot Clamp Tool

- Allows for proper installation of CV boot
- Crimps joints while with center pushing feature
- Use 1/2" drive ratchet or torque wrench
- High leverage design



Cat. No.	Drive Tang Size	Product Weight
3955	1/2 in	1.25 lb

Macpherson Strut Spring Compressor

- Use this tough tool for quick and easy replacement of struts, springs and shock absorbers
- Compress springs both on or off the vehicle with hand or power tools
- Maximum capacity: 6" outside diameter
- Wire diameter: 5/8"
- Caution: follow instructions provided with this tool



Cat. No.	Size	Product Weight
3387	6" OD 5/8" Wire Diameter	6.47 lb

CV Joint Boot Clamp Tightening Wrench

- Works by hand or ratchet with 1/2" socket
- Includes built in cutter
- Use wrench to securely fasten Band-It® style free end clamps, roll band and clips or Band-It Jr[®] style pre-formed CV boot clamps
- Mandrel tightens the clamp, holding it in place until the ears of the clamp are folded down
- Use built in cutter to remove excess band material

Cat. No.	Fits Tool	Product Weight
3191D	1/2" Socket	0.55 lb

10 Pc. Clutch Aligning Set

- Align single disc clutches on American and imported cars, light trucks and tractors
- Adapter fits through clutch plate and into pilot bushing or bearing
- Tapered cone fits into clutch hole and aligns clutch plate properly Set includes shaft and 8 two-stepped pilot bearing adapters
- covering 16 sizes
- Plate aligning cone has 1-1/8" maximum diameter taper

Cat. No.	Included Storage	Product Weight		
2420D	Blow Mold	2.08 lb		
Description	Size		Description	Size
Pilot Bushing Cone Taper	.734" - 1.17" and 18.64m	m - 29.72mm	Black Adapters for Domestic	.561" & .590" 14.2mm & 15mm
Zinc Adapter for Imports	.472" & .500" 12mm & 12	2.7mm	Black Adapters for Domestic	.749" & .787" 19mm & 20mm
Zinc Adapter for Imports	.622" & .641" 15.8mm &	16mm	Black Adapters for Domestic	.812" & .874" 20.6mm & 22.2m
Zinc Adapter for Imports	.688" & .710" 17.4mm &	18mm	Black Adapters for Domestic	.984" & 1.181" 25mm & 30mm
Zinc Adapter for Imports	.826" & .875" 21mm & 22	2.2mm		

Seal Puller

- Removes oil and grease seals on automobiles and light trucks
- 2 tip sizes for most applications
- Insert tip behind seal and use leverage to remove
- Caution: Do not use as a striking tool
- Caution: For intended use only

Cat. No.	Size	Handle Ler
3245	1 in 1-1/4 in	4.75 in

Steering Wheel Puller Kit

- Pulls steering wheels on most US and imported cars
- Includes special bolts (5/16"-18 UNC) for use on GM vehicles with SIR units
- Floating swivel on center screw prevents damage to steering column Five sets of bolts included (3/8"-16" UNC, 5/16"-18" UNC, 5/16"-24" UNF,
- 1/4"-28" UNF, and 8mm x 1.25mm)
- Will also remove crankshaft pulleys on Chrysler 2.2L and 2.5L engines

Cat. No.	Description	
2291D	Steering Wheel Puller Kit	1/4-28 UNF 3/8-16

STEERING, SUSPENSION & DRIVE TRAIN



AUTOMOTIVE SPECIALTY





FORGE AHEAD