Screwdrivers





- Ergonomic handle design greatly reduces pain and discomfort associated with repetitive tasks
- Non-slip grip generates maximum torque even when wet or oily
- Anti-roll design prevents rolling on vibrating surfaces and inclines up to 15°
- Two component ComfortGrip Handle is durable and comfortable

Color-Coded

Inch

Metric

TORX®





High Torque Steel:

Up to 20% stronger, with more torque and twice the wear resistance of standard grades of steel.

FINISH OPTIONS:



Corrosion-resistant finish:

Environmentally safe, provides better tool grip, resists solvents and is 5 times more corrosion resistant than competitor finishes.



Next generation chrome finish:

Traditional plated tool look with superior protection and durability.



FOR STATE OF STATE O

Superior protection and durability over traditional chrome and the look and shine of real gold.

Attention to Detail

To create a superior screwdriver, Bondhus gives great attention to detail. The ComfortGrip handle is more comfortable and features a better grip than typical screwdrivers. Bondhus is also the only company to match the size of our screwdriver handles to the screwdriver blade's maximum torque.



The Bondhus ComfortGrip handle features a durable thermoplastic core wrapped in cushioned rubber for increased comfort and torque.



Bondhus handles are designed and sized to match the torque capacity of each blade tip.



Ergonomically designed handles deliver maximum torque with unrivaled comfort and grip.



Slight texture of handle helps retain grip, even when hands are wet or oily.

TORX® and TORX PLUS® are trademarks of Acument Intellectual Properties, LLC

Screwdrivers

Ball End Screwdrivers

- ProGuard™ Finish -

- Ball End inserts into screw at a 25° angle
- Ergonomic handle design
- Non-slip grip
- Two component handle with tough inner core and cushioned rubber exterior
- Anti-roll design







Handles are color coded for easy recognition

Yellow=Inch Red=Metric



Sets	PART#	MODEL#	PCS	LENGTH	CONTENTS	QTY	LIST
Inch	10645	BSX7	7	Standard	5/64, 3/32, 7/64, 1/8, 9/64, 5/32, 3/16"	1	
111011	10632	BSX8S	8	Standard	.050, 1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32"	1	
	10633	BSX8	8	Standard	7/64, 1/8, 9/64, 5/32, 3/16, 7/32, 1/4, 5/16"	1	
	10637	BSX13	13	Standard	.050, 1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32, 3/16, 7/32, 1/4, 5/16, 3/8"	1	
	10737	BSX11L	11	Long	5/64, 3/32, 7/64, 1/8, 9/64, 5/32, 3/16, 7/32, 1/4, 5/16, 3/8"	1	
Billio India	10686	BSX6M	6	Standard	1.5, 2, 2.5, 3, 4, 5mm	1	
Metric	10687	BSX7M	7	Standard	1.27, 1.5, 2, 2.5, 3, 4, 5mm	1	
	10699	BSX9M	9	Standard	1.5, 2, 2.5, 3, 4, 5, 6, 8, 10mm	1	
	10733	BSX8ML	8	Long	2, 2.5, 3, 4, 5, 6, 8, 10mm	1	



10637

	**	=	· -	<u></u>	<u> </u>		SINGLE PA	TAGGE	ED/BARCODED	**	· • =	· -	<u></u>	<u> </u>	SINGL	E PACKAGING PACKAGED
Singles	SIZE	INCH	MM	INCH	MM	PART#	QTY LIST EA	PART#	QTY LIST EA	SIZE	INCH	MM	INCH	MM	PART#	QTY LIST EA
	Star	nda	rd							Lon	g					
Inch	.050 1/16 5/64	2.4 2.5 2.6	60 64 67	4.1 4.7 4.8	104 118 122	10602 10603 10604	2 2 2	40602 40603 40604	2 2 2	- - 5/64	4.3	- - 110	- 6.5	- - 164	- - 10704	- - 2
	3/32 7/64 1/8	2.8 2.9 3.1	71 74 80	5.2 5.3 6.6	132 136 168	10605 10606 10607	2 2 2	40605 40606 40607	2 2	3/32 7/64 1/8	4.8 5.9 6.4	122 151 164	7.2 8.4 9.9	184 212 252	10705 10706 10707	2 2 2
	9/64 5/32 3/16 7/32	3.3 3.6 3.7 4.2	91 94	6.8 7.9 8.0	171 201 204 230	10608 10609 10610 10611	2 2 2 2	40608 40609 40610 40611	2 2	9/64 5/32 3/16 7/32	6.9 7.4 7.9 8.4	176 189 202 214	10.4 11.8 12.3 13.3	264 299 312 337	10708 10709 10710 10711	2 2 2 2
	1/4 5/16 3/8	5.0 5.6	107 126 142 164	9.0 9.8 10.4 11.3	249 265 287	10612 10613 10614	2 2 2 2	40612 40613 40614	2 2 2 2	1/4 5/16 3/8	8.9 9.5 9.9	214 227 241 252	13.3 13.7 14.3 14.8	349 364 376	10712 10713 10714	2 2 2
	7/16 1/2	7.6 8.6	194 217	12.5 13.4	317 340	10615 10616	1 1	-	-	- -	- -	- - -		- -		-
	Stai	nda	rd							Lon	g					
Metric	1.27 1.5 2.0	2.4 2.6 2.8	60 66 72	4.1 4.7 5.0	104 120 127	10649 10650 10652	2 2 2	40649 40650 40652	2 2 2	- - 2.0	- - 4.0	- 102	- 6.2	- - 157	- - 10752	- - 2
	2.5 3.0 3.5	2.7 3.3 3.5	69 83 88	5.1 6.7 6.9	130 171 176	10654 10656 10658	2 2 1	40654 40656	2 2 -	2.5 3.0	4.3 6.2	110 158	6.7 9.7	171 247	10754 10756	2 2 -
	4.0 4.5 5.0	3.7 4.3 4.3	95 109 109	8.1 8.6 8.6	205 218 219	10660 10662 10664	2 1 2	40660 - 40664	2 - 2	4.0 - 5.0	7.0 - 7.8	179 - 198	11.4 - 12.1	288	10760 - 10764	2 - 2
	5.5 6 7	5.0 5.4 5.7	126 137 145	9.3 10.2 10.5	236 260 268	10666 10668 10670	1 2 1	40668	2	- 6 -	8.6	218	13.4	341	10768	2
	8 9 10	6.4 6.9 7.3	162 175 184	11.2 11.7 12.1	286 298 307	10672 10674 10676	2 1 2	40672	2 - 2	8 - 10	9.3	237 - 259	14.2 - 15.0	360 - 382	10772 - 10776	2 - 2



For Extra Long Length Singles see page 44

