



CP6500-RSR



2 DROPS OF OIL (CP PROTECTO-LUBE) WILL PROTECT YOUR AIR MOTOR FROM COROSION AND INCREASE TOOL LIFE

THE OIL BATH CLUTCH MECHANISM GUARANTEES A LOW LEVEL OF FRICTION WHICH INCREASES CLUTCH COMPONENT LIFETIME

## CP6500-RSR



THE BEST HEAVY-DUTY 1/2" FOR THE TOUGHEST JOBS !

### FEATURES

- CP's patented double dog clutch with oil bath
- Aluminum body & steel clutch housing
- Regulator 4 settings & One-hand reverse

### BENEFITS

- Operator comfort and control with a 4-position regulator
- Reliable double-dog clutch in oil bath & durable housing
- Compact 3-part construction for easy maintenance



CP6500-RSR

### CP6500-RS

Same features as CP6500-RSR with pin type socket retainer



| Standard Sockets kit 1/2" |                     |              |
|---------------------------|---------------------|--------------|
| Model                     | Part Number         | Set Quantity |
| SS4114 metric             | <b>894 016 4458</b> | 14           |
| SS4013 imperial           | <b>894 016 4465</b> | 13           |

See more information about sockets on page 32-33



See accessories and dimensions on pages 28 to 30



| MODEL      | PART NUMBER    | DRIVE | BLOWS PER MIN | FREE SPEED | WORKING TORQUE (FW) |         | MAX TORQUE (REV) |     | NET WEIGHT |     | LENGTH |     | AIR CONS. @LOAD |      | VIBRATION LEVEL ISO 28927 (M/S2) |     | SOUND PRESS. ISO 15744 - dB(A) | SOUND POWER | AIR INLET |
|------------|----------------|-------|---------------|------------|---------------------|---------|------------------|-----|------------|-----|--------|-----|-----------------|------|----------------------------------|-----|--------------------------------|-------------|-----------|
|            |                |       |               |            | in.                 | rpm     | ft.lb            | Nm  | ft.lb      | Nm  | lb     | kg  | in.             | mm   | cfm                              | l/s |                                |             |           |
| CP6500-RS  | <b>T025214</b> | 1/2   | 1,320         | 6,400      | 125-502             | 170-680 | 625              | 850 | 5.8        | 2.7 | 7      | 178 | 25              | 11.8 | 8                                | 2.5 | 96                             | 107         | 1/4       |
| CP6500-RSR | <b>T025216</b> | 1/2   | 1,320         | 6,400      | 125-502             | 170-680 | 625              | 850 | 5.8        | 2.7 | 7      | 178 | 25              | 11.8 | 8                                | 2.5 | 96                             | 107         | 1/4       |

All models: Hose int. 3/8" (10mm) - @90 PSI (@6.3 Bar)

Listed specifications are for reference only. Please check documents in each tool.