# **3" Diameter Sander/Buffer, Buffer**

# .2 hp, Air-Powered Buffing Tools

# For Repair of Sanding Scratches on Clearcoat

3/16" (5 mm) Dia. Orbit

Rotary Motion

## 3" (76 mm) Sander/Buffer

#### Model 69540 12,000 RPM

- Dual-purpose tool offers random orbital sanding and rotary buffing.
- · Repairs dust nibs and blemishes on paints and clear coats.
- · Also used to repair hazy/cloudy headlights, and other clear/colored acrylic surfaces.
- 3" (76 mm) diameter allows use on contoured surfaces and tight areas.
- In rotary mode, offers all the benefits of model 69550 below.

#### 3" (76 mm) Rotary Buffer Model 69550 12,000 RPM

- · Accepts 3" (76 mm) wool and foam buff pads.
- Runs at 12,000 RPM free-speed, then slows to under 4,000 RPM in use.
- Ideal for buffing door/window columns and posts, plus recessed areas and contoured surfaces.
- · Lightweight, palm-style design offers great comfort and control.
- · Adjustable speed regulator included.

Model

69540

69550



69550

Sound Level **Maximum Air Flow** Hose I.D. Size Motor Motor Sound Level Air Inlet Weight Height Lenath Number hp (W) **RPM** (Sanding) (Buffing) SCFM (L/Min) Inch (mm) Thread Pound (kg) Inch (mm) Inch (mm) 1/4" NPT .2 (149) 12,000 71 dB(A) 74 dB(A) 12 (334) 1/4 (6) 1.5 (.67) 6.1 (154) 3.7 (94) .2 (149) 12,000 N/A 74 dB(A) 12 (334) 1/4 (6) 1/4" NPT 1.5 (.67) 6.1 (154) 2.6 (70)

Tune-Up Kit: No. 96221 (page 267) • Additional Specifications: Air Pressure 90 PSIG (6.2 Bar)

# **Cut & Polish Rotary/Random Orbital Head Offers Both ROTARY and RANDOM ORBITAL Action**

### For Buffers up to 3.200 RPM

- Run pad in rotary (cut) mode for initial buffing and removing dust nibs, light scratches, oxidation and "orange peel." Then switch to random orbital (polish) mode for buffing to a swirl-free finish with no "haze" or "halo" effects!
- Offered in three female thread sizes, to fit buffers up to 3,200 RPM.
- Includes 50855 Hook-Face Backing Pad to accept wool, foam and terry cloth bonnets, in diameters of 7" (178 mm) and 8" (203 mm).
- Also includes 90082 Natural Sheepskin Polishing Bonnet, 8" (203 mm) diameter, and assorted wrenches.

Model 61384 5/8"-11 Female Thread Model 61385 M14x2 Female Thread Model 61383 M16x2 Female Thread





