

DynaPen Filer Kit

- Ideal for intricate deburring on delicate parts.
- Powers files at 14,000 strokes a minute, in short stroke length of .007" (.018 mm).
- Air line swivels 360° for great maneuverability, especially on contoured parts.
- One-touch on/off button, conveniently mounted to air line.
- Tool also accepts optional collet sizes of 1/16" (51780) and 3/32" (51674).

10844 Kit

- Includes 10832 DynaPen with 51673 Collet Insert (3 mm), 51659 Collet Insert (1/8"), 95731 Wrench, 90900 Straight File, 90901 Curved File and 90930 Half-Round File.

Model 10843

- Tool includes 51659 Collet Insert (1/8") only.



**ASK ABOUT
KITS WITH
CHISELS AND
SCRIBE POINTS!**



Model Number	Motor RPM	Stroke Length Inch	Maximum Air Flow SCFM	Air Pressure PSIG	Collet Size	Weight Pound	Length Inch	Diameter Inch	Hose Length Inch
10832	14,000	.007	7	90	3 mm	.57	4.25	.9	56


AutobradeRed® FOR THE VALUE-MINDED PRO

Auto File II Abrasive Belt Tool

Model 18100

3/4" Wide

- Includes 11206 Contact Arm for 3/4" x 18" long coated abrasive and non-woven nylon belts. 1/2" x 18" long belts also fit.
- Excellent multi-purpose tool for grinding sharp metal edges, rusted bolts, welds, etc. Works well on composites, blending, scuffing grooves and contours. Hundreds of uses in every shop!



Additional contact arms available – call for details.

Four-In-One Versatility Kit

18025

1/4" Die Grinder • 3" Cut-Off Tool
Belt Sander • 3" Disc Sander

- Quick and convenient, easy to change accessories. A must for all shops.
- Includes: 18100 basic tool, .5 hp gearless 20,000 RPM motor, front exhaust, 7° offset composite handle with safety-lock throttle; 50010 Collet; 50292 Cut-Off Guard; 50269 Flange; 51347 3" Backing Pad (3/8"-24); 15352 Drive Wheel; 40014 Belt Housing Assembly; 11206 Contact Arm Assembly; 94300 Dynaswivel®; wrenches for accessory changes; sample abrasive belt and 3" abrasive disc; deluxe storage/carrying case.



Model Number	Motor hp	Motor RPM	Sound Level	Maximum Air Flow CFM/SCFM	Air Inlet Thread	Hose Size Inch	Air Pressure PSIG	Weight Pound	Length Inch	Height Inch
18100	.5	20,000	79 dB(A)	3/22	1/4" NPT	3/8	90	2.8	15	5

Accessories

Filter-Regulator-Lubricator

- Provides accurate air pressure regulation, two stage filtration of water/contaminants and lubrication of pneumatic components.

Filter

- Five-micron filter element is standard.
- Manual push-button drain easily discharges contaminants.

Part Number	Air Inlet Thread
10671	1/2" NPT



Regulator

- Compensation built into unit responds faster to changes in incoming pressure and flow.
- Built-in PSI pressure dial gauge.

Part Number	Air Inlet Thread
10673	1/2" NPT



Lubricator

- Built-in check valve permits tool to be filled with oil without having to turn off air pressure.
- Adjustable oil drop to meter amount of oil into air system.

Part Number	Air Inlet Thread
10675	1/2" NPT



Each unit includes two bushings for easy conversion to 3/8" NPT.

Additional Specifications: Maximum Operating Pressure 145 PSIG.

Filter-Regulator

- Unit has modular connections with mounting brackets for easy installation.

Part Number	Air Inlet Thread
10677	1/2" NPT



Regulator-Lubricator

- Unit has modular connections with mounting brackets for easy installation.

Part Number	Air Inlet Thread
10679	1/2" NPT



Filter-Regulator-Lubricator

- Unit has modular connections with mounting brackets for easy installation.

Part Number	Air Inlet Thread
10681	1/2" NPT



FRL Flow Characteristics

Flow • SCFM (LPM)	Pressure Drop Across FRL • PSI (Bar)
15 (425)	2.0 (.14)
30 (850)	3.0 (.21)
45 (1274)	6.0 (.41)
60 (1699)	7.0 (.48)
75 (2124)	8.0 (.55)

Dynabrade Locking-Type Pads

- Locking-type sanding pads available in three diameters.
- Constructed of durable, non-marring material.
- "Type-R" locking-type abrasive discs thread directly into Dynapad® back-up pad, allowing quick change of abrasives.



Part No.	Diameter	Female Thread	Pad MOS RPM
51344	2"	1/4"-20	30,000
51345	2"	3/8"-24	30,000
51346	3"	1/4"-20	20,000
51347	3"	3/8"-24	20,000
50192	4"	3/8"-24	12,000

3" to 7" Hook-Face Buffing Pads

- Use on two-hand or palm-style buffers.



Size	Part No.	Description	Type/Color
3"	90027	Terry Cloth	N/A
3"	90028	Synthetic Wool	N/A
3"	90038	Foam Flat Face	Polishing/White
3"	90044	Foam Flat Face	Cutting/Yellow
3"	90080	Natural Wool	Sheepskin
3-1/2"	90034	Natural Wool	Sheepskin
5"	90036	Wool	Thick Pile
5"	90040	Foam Flat Face	Polishing/White
5"	90045	Foam Flat Face	Cutting/Yellow
5"	90081	Natural Wool	Sheepskin
6"	90046	Foam Flat Face	Cutting/Yellow
6"	90047	Foam Flat Face	Polishing/White
7"	90082	Natural Wool	Sheepskin