# **Sanding Pads** For All Random Orbital Sanders / DynaLocke®

• All pads: 5/16"-24 male thread. • 13,000 RPM maximum rated. • Fit most brands of orbital sanders. • Perfectly balanced for use with Spirit sanders!



# 3/8" Thick, Low Profile

PSA					
Pad		5" Diameter		6" Diameter	
Construction	Density	Non-Vacuum	Vacuum	Non-Vacuum	Vacuum
Rubber	Medium	50630	50631	50632	50633
Rubber Post Pattern	Medium	-	50695	-	50696
Value Urethane	Medium	56205	56207	56206	56208
Premium Urethane	Soft	56102	56100	56103	56101
Premium Urethane	Medium	56106	56104	56107	56105
Premium Urethane Channel-Vac	Soft	_	56251	_	56261
Premium Urethane Channel-Vac	Medium	-	56252	-	56262

## **Hook-Face, Short Nap**

Premium Urethane	Soft	56157	56155	56158	56156
Premium Urethane	Medium	54325	54326	54327	54328
Premium Urethane Channel-Vac	Soft	_	56253	_	56263
Premium Urethane Channel-Vac	Medium	_	56250	_	56260

### Hook-Face, Long Nap (For Non-Woven Nylon)

Rubber	Medium	50605	50607	50606	50610

# 5/8" Thick, All Premium Urethane

• A thicker pad conforms more easily to curved and contoured surfaces and makes it ideal for featheredging.

#### **PSA**

	3" Diameter	3-1/2" Diameter	5" Dia	meter	6" Diam	neter
Density	Dual Purpose	Dual Purpose	Non-Vacuum	Vacuum	Non-Vacuum	Vacuum
Soft	56086	56097	56185	56186	56187	56188
Medium	56084	56098	56175	56176	56177	56178
Channel-Vac Soft	-	-	_	56256	-	56266
Channel-Vac Medium	-	-	_	56254	-	56264

# **Hook-Face, Short Nap**

Soft	_	54311	56195	56196	56197	56198
Medium	56087	54313	56180	56181	56182	56183
Channel-Vac Soft	-	-	-	56257	_	56267
Channel-Vac Medium	-	-	-	56255	_	56265

#### Hook-Face, Long Nap (For Non-Woven Nylon)

Medium 56090 54314 – – – –	Medium	56090		_	-	_	-
----------------------------	--------	-------	--	---	---	---	---