

DYNALOCKE®



The DynaLocke® is truly “two tools in one,” easily changing from a rotary Disc Sander to Random Orbital Sander with a turn of the dial. Repair technicians can increase their productivity by accomplishing paint stripping and feather edging applications with one tool.

FEATURES

- ▶ Switch is recessed within tool grip for comfort and to prevent accidental engaging
- ▶ Speed control lever is conveniently located for easy thumb adjustment
- ▶ Insulated tool housing reduces cold air transmission to the hand

ROTARY MOTION

For Stripping
and Blending



3/16" DIA. ORBIT

For General
Sanding



Model 58436

SPEED

12,000 RPM

POWER

0.45 hp (336 W)

DIAMETER

3", 5", 6"

Model Number	Diameter Inch (mm)	Sound Level	Maximum Air Flow SCFM (L/Min)	Weight Pound (kg)	Height Inch (mm)	Length Inch (mm)
58460	3 (76)	81 dB(A)	23 (651)	2.35 (1.0)	5.37 (137)	10.31 (263)
58461	3 (76)	86 dB(A)	23 (651)	2.35 (1.0)	5.37 (137)	10.31 (263)
58430	5 (127)	82 dB(A)	23 (651)	2.7 (1.2)	5.12 (131)	11 (280)
58435	6 (152)	82 dB(A)	23 (651)	2.8 (1.2)	5.12 (131)	11 (280)
58436	6 (152)	85 dB(A)	23 (651)	2.7 (1.2)	5.12 (131)	11 (280)

Additional Specifications: Air Inlet Thread 1/4" NPT • Hose I.D. Size 1/4" • Air Pressure 90 PSIG
Maximum Air Flow 23 SCFM (651 L/Min) • Tool Thread 5/16" - 24 Female



**LIFETIME
WARRANTY**

TECH TIP

Tool should be completely stopped before changing sanding action.

BENEFITS



The DynaLocke® quickly strips paint to bare metal when set to rotary mode and converts to random orbital to complete the feather-edging portion of the application.