

MAX FLOW AIR HOSE ASSEMBLY

LIGHTWEIGHT AIR LINES – 5/16" I.D.

- ▶ 66% lighter than conventional hoses
- ▶ Great flexibility and tool maneuverability, reduces operator fatigue
- ▶ Includes reusable fittings, ensuring air line integrity
- ▶ Narrow bending radius prevents "choking" of air tool



Part Number	Length Feet (Meters)	Line I.D. Inches (mm)	Line O.D. Inches (mm)	Fittings Included
94730	5 (1.5)	5/16" (8)	1/2" (13)	Male (1/4") / Male (1/4")
94731	12 (3.7)	5/16" (8)	1/2" (13)	Male (1/4") / Male (1/4")
94732	25 (7.6)	5/16" (8)	1/2" (13)	Male (1/4") / Male (1/4")
94733	Specify length	5/16" (8)	1/2" (13)	Order 94734 for Male (1/4") / Male (1/4") installed

Part Number	Connects to Inside Diameter	Connection Thread
94897	5/16" (8)	1/4" NPT Male



DYNAJET IN-LINE BLOW GUN

SAFETY TIP DESIGN

- ▶ Blow gun permanently mounted between coupler and air hose to purge air line of water and contaminants
- ▶ Durable aluminum construction, weighs only 2 oz. (.06 kg)
- ▶ Reduces line pressure down to 30 PSIG (2 Bar)
- ▶ Meets O.S.H.A. requirements of special relief hole in nozzle, which limits pressure to 30 PSIG (2 Bar) when dead-ended and used on an air line of 150 PSIG (10.3 Bar) or less
- ▶ Ideal to blow debris from work surface



Proper Installation for DynaJet Blow Gun Connection



Part Number	Thread Size	Weight	Recommended Air Flow Range SCFM (L/Min)
94467	1/4" Female NPT	.06 kg	up to 35 SCFM (991 L/Min)

10.3 Bar (150 PSIG) maximum