



AIRCUT® 15C - PORTABLE PLASMA CUTTING SYSTEM



TurboTorch® offers accessories to help improve cutting performance. Look for the TurboTorch mark on your plasma consumable parts for genuine TurboTorch consumables. This unit comes standard with a built-in internal air compressor that can be plugged in anywhere. Easy to use with superior cutting capacity.

Features:

- 25% more cutting power provides 25% faster cut speeds than the competition
- Lightweight only 29 lbs (13.2 kg) nearly 50% lighter than the competition



AIRCUT 15C Portable Plasma Cutting System Part No. 1-1110-1

System Includes:

- Power Supply with 20 ft (6.1 m) Lead
- PCH-10 Torch with 70 degree Head
- 8.5 ft (2.6 m) Input power cable and plug
- 19.5 ft (5.9 m) Work Cable
- Operating Manual

| Part No. | Product Description |
|----------|--|
| 1-1110-1 | AirCut Portable Plasma Cutting System |
| 2-1020 | PCH-10 Torch (70°) with 20 ft (6.1 m) Lead |
| 7-8910 | Cutting Guide Kit |
| 9-1260 | 20 ft (6.1 m) Leather Leads Cover |
| 9-6003 | Shield Cup |
| 9-6099 | Tip - Air, 0.028 Orifice |
| 9-6005 | Gas Distributor |
| 9-6006 | Electrode |

Torch Consumables



SPECIFICATIONS

| | |
|--------------------------|----------------------------|
| Maximum Output | 15A @ 120V Fixed |
| Maximum Cut Capacity | 3/16" (5 mm) @ 120V |
| Recommended Cut Capacity | 1/8" (3 mm) @ 120V |
| Gas Type | Air Compressor (built-in) |
| Pilot | CD Start |
| Amperage Draw | 12A @ 120V |
| Duty Cycle (@40°C) | 35% @ 15A |
| Power Source Weight | 29 lbs (13.2 kg) |
| Primary Power | |
| Primary Voltage | 120 VAC (± 10%), |
| Number of Phases | Single Phase |
| Supply Frequency | 50/60 Hz |
| Power Cord | 19.5 ft (5.9 m) |
| Torch Information | |
| Torch Model | PCH-10 Torch with 70° head |
| Air Pressure | 75 psi (5.2 bar) |
| Air Flow | 3.2 cfm (91 lpm) |