Accessories

Pressure Cups



Low Pressure Cup Assembly

PN 6680

- Designed for use with Sharpe pressure feed
- 1 quart capacity
- Clamp type assembly
- Order with 6 ft hose (PN 7130)

- Inlet 3/8 in npsm (f) swivel nut
- Max Pressure: 10 psi
- Cup Assembly (PN 6610)
- Replacement Gasket (PN 20994)
- Air 1/4 in NPS (m)



Model 7004 2-Quart Pressure Cup

- For use with any pressure feed spray gun when more than one quart of material is required
- Replacement gasket (PN U42002)
- Wide mouth for easy cleanup
- Cup pressure regulator allows for fluid adjustment from 0-50 psi

Pressure Pots



2.5 Gallon Pressure Pot Single Regulator

PN 24A555

- 1610 Air regulator used to regulate fluid pressure
- Tank capacity: 2.5 gal (9.5 l)
- Accessory hose to use 7210 or 7220
- Includes one (1) tank liner
- Replacement tank liner: 112077 (5-pack) 112078 (25-pack)

- Max working pressure: 50 psi (350 kPa, 3.5 bar)
- Pressure relieve valve setting: 50 psi (350 kPa, 3.5 bar)
- Air inlet size: 1/4 npt (m)
- Fluid outlet size: 3/8 npsm (m)
- Air outlet size: 1/4 npt (m)
- Height: 21 in (533 mm)
- Weight: 11 lb (5 kg)
- Instruction Manual: PN 313291
- Reference p. 50



2.5 Gallon Pressure Pot **Dual Regulators**

PN 24A557

- 1610 Air regulator used to regulate fluid pressure
- 1630 Air regulator used to regulate fluid pressure
- Tank capacity: 2.5 gal (9.5 l)
- Accessory hose to use 7210 or 7220
- Includes one (1) tank liner
- Replacement tank liner: 112077 (5-pack)

112078 (25-pack)

- Max working pressure: 50 psi (350 kPa, 3.5 bar)
- Pressure relieve valve setting: 50 psi (350 kPa, 3.5 bar)
- Air inlet size: 1/4 npt (m)
- Fluid outlet size: 3/8 npsm (m)
- Air outlet size: 1/4 npt (m)
- Height: 21 in (533 mm)
- Weight: 11 lb (5 kg)
- Instruction Manual: PN 313291
- Reference p. 51