

# Impact Sockets, Chisels & Attachments











# GP is Everything Impact.

Grey Pneumatic (GP) through our distributors supplies the world's automotive, industrial, assembly, mining, maintenance, construction, and energy industries with heavy duty, high quality impact and specialty sockets. We carry a complete line of Impact Socket sets and individuals from 1/4" drive thru 2-1/2" and #5 spline drive with hex sizes up to 8". We also offer a large selection of star impact drivers, impact hex drivers, triple square drivers, torque limiting extensions plus Impact chisels and accessories.

GP sockets and tools are made in Taiwan using the highest quality chrome-molybdenum alloy steel and state-of-the-art manufacturing processes and equipment. Thorough and exact heat treatment, as well as rigid quality control, ensures the correct balance of strength and durability to deliver outstanding performance at the most competitive cost.

GP Tools are available through Automotive and Industrial warehouse distributors, tool stores, mobile tool truck dealers, tire equipment and supply warehouses and other sources that service these markets.

GP offers Fast and Reliable service to all of our distributors and their customers.



GP Tools carry a Lifetime Warranty.

# All GP Impact Sockets feature the GP "High Torque" Drive

#### **Benefits are:**

**Increased Strength** - Transfers the pressure from the thinnest part of the socket wall toward the thicker section, resulting in increased strength.

**Increased Torque** - Allows up to 20% more torque to be applied than on standard hex impact sockets.

**Easier Access to Tight Areas** - The shift in pressure allows us to reduce the socket wall thickness, increasing access to tight areas.

**Reduced Wear** - Our impact sockets grip the fastener across a broader contact area, reducing the chance of rounding off fasteners.



All GP Sockets feature extra-large size markings for quick identification.




GP "High Torque" drive offers many benefits.





# 1/4" Drive Adapter



Item	Female N	Male	Socket Retention	Dimensions (Inches)	
Number	End	End	Device	Α	E
938A	1/4"	3/8"	Friction Ball	.54	1.02
*See page 182 for New Reducing Sleeve Adapters					


1/4" Drive Universal Joint



Item		Socket Retention	Dimensions (Inches)			
Number	Size	Device	Α	В	Ε	_
929UJ	1/4" x 1/4"	Friction Ball	.63	.71	1.69	

# 1/4" Drive Extensions SAE





Locking

ltem		Socket Retention	Dimensions (Inches)	
Number	Description	Device	Α	E
Standard Exte	nsions			
942E	2" Extension	Friction Ball	.51	1.97
944E	4" Extension	Friction Ball	.51	3.94
946E	6" Extension	Friction Ball	.51	5.91

# Locking Extensions

These extensions feature a positive locking ball and sliding collar for quick release of sockets and accessories. Useful in hard to reach areas where a positive lock on the socket is required.

9703QL	<b>3 pc. Locking Extension Set</b> - includes 3", 6", 12"
--------	---

943QL	3" Locking Extension	.51	2.95
946QL	6" Locking Extension	.51	5.91
952QL	12" Locking Extension	.51	11.81
958QL	18" Locking Extension	.51	17.72
964QL	24" Locking Extension	.51	24.02

### Socket Retention Device Key for 1/4" Drive Adapters, Extensions & Universal Joints



# FB Friction Ball

A spring loaded steel ball that lines up with the socket retainer hole. Use caution when using this system because the socket is held in place only by spring pressure on the steel ball.

Do NOT run the tool when the socket is OFF the fastener.

