


## ProFinisher™ 600 Series - 3/16 Offset

- Random Orbital sanders with a 3/16" offset are generally used for all-around sanding tasks.
- Whether you plan to shape fillers & putties, feather-edge panels, or prep for paint, these sanders will perform a broad array of tasks.
- If your budget only allows for one sander, the 3/16" offset should be your choice.



Part No.	Pad Size/Type	Air Consumption at 90psi	Speed	Noise	Weight	Vacuum/Self-Gen.	Accessories Included	Vac Port OD
600	6" PSA	10.7 CFM	12,000 RPM	81 dBa	3lbs	No		No
600H	6" Hook	10.7 CFM	12,000 RPM	81 dBa	3lbs	No		No
603	3" Hook	10.7 CFM	12,000 RPM	81 dBa	3lbs	No		No
610*	6" Hook Multi-hole	10.7 CFM	12,000 RPM	84 dBa	3lbs	Self-Gen		1"
620**	6" Hook Multi-hole	10.7 CFM	12,000 RPM	81 dBa	3lbs	Vacuum		1"
623**	3" Hook 3-hole	10.7 CFM	12,000 RPM	81 dBa	3lbs	Vacuum		1"

## ProFinisher™ 700 Series - 5/16 Offset

- When time is money and you want the fastest sander available; turn to 5/16" offset sanders.
- These sanders deliver the fastest cut (up to 30% faster) while maintaining low vibration for exceptional operator comfort and safety.



Part No.	Pad Size/Type	Air Consumption at 90psi	Speed	Noise	Weight	Vacuum/Self-Gen.	Accessories Included	Vac Port OD
700	6" PSA	10.7 CFM	12,000 RPM	81 dBa	3lbs	No		No
700H	6" Hook	10.7 CFM	12,000 RPM	81 dBa	3lbs	No		No
703	3" Hook	10.7 CFM	12,000 RPM	81 dBa	3lbs	No		No
710*	6" Hook Multi-hole	10.7 CFM	12,000 RPM	84 dBa	3lbs	Self-Gen		1"
720**	6" Hook Multi-hole	10.7 CFM	12,000 RPM	84 dBa	3lbs	Vacuum		1"
723**	3" Hook 3-hole	10.7 CFM	12,000 RPM	81 dBa	3lbs	Vacuum		1"

## ProFinisher™ Random Orbital Accessories

### Replacement Pads

Part No.	Description
750	Low Profile 5" PSA Pad (optional)
751	Low Profile 5" Hook Pad (optional)
752	Vacuum, Low Profile 5" Hook Pad (optional)
760	Low Profile 6" PSA Pad
761	Low Profile 6" Hook Pad
762	Vacuum, Low Profile 6" Hook Pad
5101	1" Hook Pad for Models: 503, 603 & 3501 (optional)
5103	3" Hook Pad for Models: 503, 603 & 3501
5143	3" 3-Hole Vacuum Hook Pad for Models: 523 & 623

### Accessories

Part No.	Description
780	Coaxial Hose Assembly
800	Pad Wrench
810	Vacuum Conversion Kit **
850	3/32" Offset Replacement Motor
860	3/16" Offset Replacement Motor
870	5/16" Offset Replacement Motor
1350-4	Disposable Dust Bag Complete
1529A	"For Aluminum Only" Red ProFinisher Trigger
5301-2	Connector (1 1/2" OD Vac line)
5301-5	ProFinisher™ Connector (1" OD Vac line)



780



\* Complete Dust bag and connector required on Models 510, 610 & 710

\*\* Models 520, 523, 620, 623, 720, 723 & 810 Kit require either 5301-2 or 5301-5 to complete vacuum connection

# Straightline Sanders




All Hutchins Straightline sanders have dual cylinders with a common piston and vertically-engaged, twin-drive gears. This double rack and pinion gear assembly gives twice normal gear contact for maximum balance, thrust and longevity.



**2000**  
15/16" Stroke



**2025**  
13/16" Stroke



**2023**  
13/16" Stroke




**4920**  
15/16" Stroke



**8623**  
13/16" Stroke

- Straightline sanders are used for shaping fillers and putties and for achieving a perfectly flat surface.
- The Linear motion replicates hand sanding with a block.



Part No.	Pad Size/Type	Air Consumption at 90psi	Speed	Noise	Weight	Vacuum/Self-Gen.	Accessories Included	Vac Port OD
2000	2 3/4" x 16" Clip/PSA	6.2 CFM	3,000 SPM	90 dBa	6lb 4oz	No		No
2000-4H	4 1/2" x 16" Hook	6.2 CFM	3,000 SPM	90 dBa	6lb 4oz	No		No
2023	2 3/4" x 8" PSA	4.4 CFM	3,000 SPM	78 dBa	4lb 13oz	No		No
2025	4 1/2" x 9" Clip/PSA	4.4 CFM	3,000 SPM	78 dBa	4lb 14oz	No		No
4920*	2 3/4" x 16" PSA 18-hole	6.2 CFM	3,000 SPM	88 dBa	6lb 2oz	Vacuum		1"
4920-4H*	4 1/2" x 16" Hook 18-hole	6.2 CFM	3,000 SPM	88 dBa	6lb 2oz	Vacuum		1"
8620	2 3/4" x 16" PSA 18-hole	6.0 CFM	3,000 SPM	87 dBa	7lb 1oz	Self-Gen	5862/1350-4	1 1/2"
8623	2 3/4" x 8" PSA 8-hole	4.3 CFM	3,000 SPM	78 dBa	5lb 12oz	Self-Gen	5862/1350-4	1 1/2"
8625	4 1/2" x 9" Clip/PSA 8-hole	4.3 CFM	3,000 SPM	78 dBa	5lb 12oz	Self-Gen	5862/1350-4	1 1/2"

## Straightline Accessories

### Replacement Pads

Part No.	Description
5002-H	2 3/4" x 16" Hook Pad
5003	2 3/4" x 16" PSA Pad
5005	4 1/2" x 16" PSA Pad
5005-H	4 1/2" x 16" Hook Pad
5005-HVA	Vacuum, 4 1/2" x 16" 18-hole Hook Pad
5006-H	Vacuum, 2 3/4" x 8" Hook Pad
5011	2 3/4" x 11" PSA Pad
5011-H	2 3/4" x 11" Hook Pad
5013	Vacuum, 2 3/4" x 16" 18-hole PSA Pad
5013-H	Vacuum, 2 3/4" x 16" 18-hole Hook Pad
5023	2 3/4" x 8" PSA Pad(PSA paper only)
5023-H	2 3/4" x 8" Hook Pad

### Replacement Pads

Part No.	Description
5025	4 1/2" x 9" Clip/PSA Pad
5025-H	4 1/2" x 9" Hook Pad

### Accessories

Part No.	Description
12027	Tune-up Kit for 2000
1350-4	Disposable Dust Bag Complete
5301-1	VA Connector Hose Fitting
5301-2	Connector (1 1/2" OD Vac line)
5862	Coaxial hose for 8620, 8623-25, 8650-60
780	Coaxial hose for current 4920, 4920H, 4920-4H



5301-2      1350-4

\*Complete Dust bag and connector optional for 4920, 4920H 4920-4H



780

\*For hook-type tools not listed, add "H" to the sander part number (i.e. 2000H comes with a hook-pad instead of PSA)

# Legacy Orbital Sanders



Orbital Action Sanders are versatile and adapt to every surface preparation need. Developed in the early 50's, this style of sander still is preferred for marine, industrial, and automotive applications. Because the fixed pad orbits an offset counterweight, fast sanding and smooth finish results can be expected.

- 3/32" offset orbitals sanders are used mainly for pre & post paint operations and are generally used for wet sanding applications.
- 3/16" offset orbitals sanders are more aggressive and used for applications requiring fast material removal and super-flat surface finishes.



3800



4932



3900



4564

Part No.	Offset	Pad Size/Type	Air Consumption at 90psi	Speed	Noise	Weight	Vacuum/Self-Gen.	Accessories Included	Vac Port OD
3800	3/16"	2 3/4" x 16" PSA/Clip	11.4 CFM	8,500+ RPM	89 dBA	5lb 5oz	No		No
3800-4H	3/16"	4 1/2" x 16" Hook	11.4 CFM	8,500+ RPM	89 dBA	6lb 5 oz	No		No
3805	3/16"	8" x 18" PSA	11.4 CFM	8,500+ RPM	89 dBA	6lb	No		No
3806	3/16"	8" x 18" Padded PSA/Clip	11.4 CFM	8,500+ RPM	89 dBA	6lb	No		No
3900	3/16"	4 1/2" x 9" PSA/Clip	11.4 CFM	8,500+ RPM	90 dBA	5lb 2 oz	No		No
4564	3/16"	3 2/3" x 7" PSA/Clip	10.4 CFM	8,500+ RPM	80 dBA	3lb 7oz	No		No
4932*	3/16"	2 3/4" x 16" PSA -hole	11.5 CFM	8,500+ RPM	91 dBA	5lb 6oz	VA/Self-Gen		1"
4932-4H*	3/16"	4 1/2" x 16" Hook Multi-hole	11.5 CFM	8,500+ RPM	91 dBA	7lb 4 oz	VA/Self-Gen		1"
4933	3/16"	4 1/2" x 9" PSA 10-hole	10.8 CFM	8,500+ RPM	88 dBA	5lb 4 oz	VA/Self-Gen		1"
8664	3/16"	3 2/3" x 7" PSA 10-hole	11.5 CFM	8,500+ RPM	88 dBA	4lb 12 oz	Self-Gen	5862/1350-4	1 1/2"

## Water Sanders

7004	3/32"	3 2/3" x 7" PSA/Clip	10.2 CFM	8,500+ RPM	76 dBA	3lb 14oz	No		No
7044	3/32"	3 2/3" x 7" Hook/Clip	10.4 CFM	8,500+ RPM	81 dBA	4lb 1oz	No	1301	No
7044-6	3/32"	6" Hook	10.4 CFM	8,500+ RPM	81 dBA	4ln 1oz	No	1301-1	No

## Orbital Accessories



7044

### Replacement Pads

Part No.	Description
1802	2 3/4" x 16" PSA Pad (Model 3800)
1802-5	Vacuum, 2 3/4" x 16" 18-hole PSA Pad (Model 4932)
1902	4 1/2" x 9" PSA/Clip Pad (Model 3900)
1902H	4 1/2" x 9" Hook Pad (Model 3900)
1902-3H	Vacuum, 4 1/2" x 9" 10-hole Hook Pad (Model 4933)
5005	4 1/2" x 16" PSA Pad (Model 3800, 3800-4)
5005H	4 1/2" x 16" Hook Pad (Model 3800, 3800-4H)
5005HVA	Vacuum, 4 1/2" x 16" 18-hole Hook Pad (Model 4932)
5802	2 3/4" x 16" Hook Pad (Model 3800)
5803	Vacuum, 2 3/4" x 16" 18-hole Hook Pad (Model 4932)
5864A	Water, 3 2/3" x 7" Hook Pad (Model 7044)
5864R	3 2/3" x 7" PSA/Clip Pad (Model 4564)
5864W	Water, 3 2/3" x 7" PSA/Clip Pad & Water Line (Model 7004)

### Replacement Pads

Part No.	Description
5864A	Water, 3 2/3" x 7" Clip Pad (Model 7044)
5866A	Water, 6" Hook Pad (Model 7044-6)

### Accessories

Part No.	Description
1301	Interface Pad, 3 2/3" x 7" 10-Hole Hook Pad (Model 7044)
1301-1	Interface Pad, 6" 6-Hole Hook Pad (Model 7044-6)
1350-4	Disposable Dust Bag Complete
5301-2	Connector (1 1/2" OD Vac line)
780	Coaxial Hose for current 4932, 4932H, 4932-4H



5301-2 1350-4  
\*Complete Dust bag and connector optional for 4932, 4932H, & 4932-4H



780

\*For hook-type tools not listed, add "H" to the sander part number (i.e. 3800H comes with a hook-pad instead of PSA)