

JUMBO CHAIN TOOL

This tool is de-signed to break roller chains up to #630 and fits all standard & O-ring chain sizes #520 to #630. Its designed to rivet chains up to #530. (not #630) Master link side plate press kit included to press on side plates on chains up to #530. (not #630) The screws and attachments are heat treated for strength and durability. The extractor pin is precisely guided by a removable guide ensuring long pin life. This may be bolted to a work bench, supported in a vise, or held by handle. When bolted to a solid surface, air or electric wrenches may be used to break chain. This tool is recommended for heavy duty use. Instructions included with tool.

No.926 - See above chain application info above for chain type and sizes.



CHAIN PRESS TOOL KIT

Since about 1990, most new chains use press-fit type side plates on the connecting links. With this type of link the side plate cannot be installed properly without the aid of this special tool. The chain manufacturers have determined a press fit adds strength to the connecting link and should always be used.

No. 925 - Used on #520 - # 530 chain with press fit connecting links either standard or o-ring style.



REPLACEMENT PRESS PLATES ONLY

No.924 - Used on tool No.925 above.



MASTER LINK PLIERS

Designed to simplify installation and removal of clip-type master links. One tip is shorter and notched to be placed on the pin which allows the longer tip to push the clip.

No.921 - Master Link Pliers.



BELT TENSION GAUGE

This compact designed tool is used to assist in properly adjusting secondary belt tension with a 10 lb.. specification. Tool has an easy to read scale. Use on all rear belt driven O.E.M. or after-market motorcycles.

No.923 - Used on all rear belt driven O.E.M. or after-market motorcycles.