KKKen-Tool

WHEREVER TIRES ARE CHANGED™

TIRE MOUNT/DEMOUNT SPOONS

Espátula para montaje/desmontaje de llantas Cuillères de montage/démontage de pneus

These tools are designed for fast and efficient tire changing. Use the 18" and 24" spoons to mount or demount passenger car, motorcycle, ATV, and light truck tires. The 30" spoons provide enough strength and leverage to work on large truck, bus, off-road vehicle, tractor, and aircraft tires.



30" (76cm) 33052

Straight (Recta | Droite)

В	T1X	32101	18" (46 cm)	11/16" (17.5 mm)	1.8 lbs (.8 kg)
	T19	32119	24" (61 cm)	11/16" (17.5 mm)	2.5 lbs (1.1 kg)
	T19A	33219	30" (76 cm)	11/16" (17.5 mm)	3 lbs (1.4 kg)
	T19M	33022	30" (76 cm)	3/4" (19 mm)	3.4 lbs (1.54 kg)
	T38	33238	30" (76 cm)	7/8" (22 mm)	4.8 lbs (2.2 kg)

Drop-Center (Combinación con base con caída | Base creuse)

С	T21R	32121	18" (46 cm)	11/16" (17.5 mm)	1.8 lbs (.8 kg)
	T21F	34121	24" (61 cm)	11/16" (17.5 mm)	2.5 lbs (1.1 kg)
	T21A	33020	30" (76 cm)	11/16" (17.5 mm)	3.1 lbs (1.4 kg)
	T21M	33024	30" (76 cm)	3/4" (19 mm)	3.4 lbs (1.54 kg)
	T21HD	34122	30" (76 cm)	7/8" (22 mm)	4.5 lbs (2.0 kg)
	Curvea	l (Curva / Co	urbe)		
D	T2X	32102	18" (46 cm)	11/16" (17 5 mm)	18 lbs (8 kg)

-	12/(52102		11/10 (17.511111)	1.0 105 (.0 kg)
	T20	32120	24" (61 cm)	11/16" (17.5 mm)	2.4 lbs (1.1 kg)
	T20A	33220	30" (76 cm)	11/16" (17.5 mm)	3.1 lbs (1.4 kg)
	T20M	33023	30" (76 cm)	3/4" (19 mm)	3.4 lbs (1.54 kg)
	T39	33239	30" (76 cm)	7/8" (22 mm)	4.5 lbs (2.0 kg)

Curved with Flat (Curva con punta plana | Courbe avec embout plat)

T22R	31820	18" (46 cm)	11/16" (17.5 mm)	1.8 lbs (.8 kg)
T22F	32420	24" (61 cm)	11/16" (17.5 mm)	2.5 lbs (1.1 kg)
T22A	33021	30" (76 cm)	11/16" (17.5 mm)	3.1 lbs (1.4 kg)
T22M	33025	30" (76 cm)	3/4" (19 mm)	3.4 lbs (1.54 kg)
T22HD	33026	30" (76 cm)	7/8" (22 mm)	3.4 lbs (1.54 kg)

SMALL TIRE MOUNT/DEMOUNT IRONS Barras para montaje/desmontaje de llantas pequeñas

Leviers de montage/démontage de petits pneus

New designs are based on popular European styles. Extended length of the flat curved sliding surface provides mounting ability comparable to much longer traditional tire irons. Sizes available for motorcycle, passenger, truck, and heavyduty tires. Designed for mounting and demounting tires. Best if used in pairs.

MOTORCYCLE/SMALL WHEEL 39805 T43A Ruedas pequeñas/de motocicleta | Motocyclette/Petites roues

Lenath: 15" (38 cm) Stock: 3/4" (19 mm) Weight: 1.8 lbs (.8 kg)



MOUNT/DEMOUNT TIRE TOOLS - SMALL TIRE 32106 T6A Herramientas para montaje y desmontaje de llantas – Llantas pequeñas

Outils de montage/démontage de pneus - Petits pneus

Length: 16-1/2" (42 cm) Stock: 5/8" (16 mm) Weight: 1.5 lbs (.7 kg) Tools are used in pairs to mount or demount small passenger, industrial,

ATV, and motorcycle tires.



TIRE IRONS - SMALL TIRE Barras para llantas – Llantas pequeñas Démonte-pneus - Petits pneus

Pro tire changing tools for small tires. Ideal for mounting and demounting motorcycle, ATV, lawn tractor, golf cart, and small tires by hand. Rounded ends will not pinch tube.

Model	ltem No.	Length	Stock	Weight
T9A	32109	9" (23 cm)	7/16" (11 mm)	.4 lbs (.16 kg)
T16A	32116	16" (41 cm)	7/16" (11 mm)	.7 lbs (.3 kg)
T9C	32110	2 pc. Carded Set - Contains: Qty. (2) T9A 9" Bars		
T16C	32117	2 pc. Carded Set - C	2 pc. Carded Set - Contains: Qty. (2) T16A 16" Bars	
T5*	32115	16" (41 cm)	7/16" (11 mm)	.8 lbs (.36 kg)
T8*	32118	16" (41 cm)	7/16" (11 mm)	.8 lbs (.36 kg)
	32114	2 Pc. Small Tire Iror Contains: Qty. (1) T	n Set 5 (32115), Qty. (1) T8 (32118)	1.6 lbs (.7 kg)

*Sturdy, comfortable plastic handles.



22" (56 cm)

28" (71 cm)

42" (102 cm)

34672

34674

34678

TS72

TS74

TS42

5/8" (2 cm)

5/8" (2 cm)

Tire Snake mounting and demounting tools for use with center post tire changers. Included with T600 Tire Changer, designed for wheels from 4" to 12". Included with T601 Tire Changer, designed for wheels from 4" to 15", the 2.5 lbs (1.1 kg)

longer length provides greater

leverage. PATENTED.



IRONMAN™ ERGONOMIC WHEEL LIFTING BAR 34950 T950 Barra ergonómica para el levantamiento de neumáticos Ironman" Barre ergonomique de levée de roue Ironman™

Length: 58" (147 cm) Stock: 1" (25 mm) Weight: 10 lbs (4.5 kg)

Reduces back strain. Easily and safely lift heavy, awkward truck tire and wheel assemblies. Extremely useful in outdoor conditions when truck tire and wheel assemblies can become wet and slippery. Lift all sizes and types of small and large heavy truck wheels: Standard sizes including 22.5" and 24.5" wheels, plus European (which have 1" lug holes), Super Wide and even the Super Single (can weigh over 400 lbs.) size. IronMan can pick them up!



DON'T RISK INJURY

ERGONOMIC: Use the leverage created by the tool - NOT YOUR BACK! Specially designed forged ends work from either side of the wheel assembly as it lays flat







Threadscrew

milled to fit

MTD wheels.

has been

Specially designed spoon end for hub side down

MANUAL TIRE CHANGERS

T601 FLOOR MOUNT 38601 Montaje de piso | Montage au sol

Height: 32" (81 cm) Weight: 31 lbs (14 kg)

Mounts and demounts a full range of tires on rim diameters from 4 to 15 inches. Tapered bearing guide positively centers straight shaft hubs of all diameters. A built-in, infinitely adjustable bead breaker works on rims up to 15" in diameter and 24" in width without disassembly. Includes a Ken-Tool exclusive, 28" Tire Snake[®] mount/demount tire tool.







WARNING: Always wear safety goggles when using hand tools.

2 lbs (.9 kg)

3/4" (19 mm) 5.3 lbs (2.4 kg)

01 TIRE IRONS (MOUNT/DEMOUNT)




IronMan™ Wheel Lifting Bar



EUROPEAN STYLE TOOLS Herramientas de estilo europeo Outils de style européan

Use on car, motorcycle, truck, and agricultural tires. Designed for mounting and demounting tires. Best if used in pairs.





Cambiadores de llantas manuales | Démonteurs de pneus manuels



T600 BENCH/RIM CLAMP MOUNT 38600 Montaje de banco/abrazadera de llantas | Montage sur banc/crapaud

Height: 16-1/2" (42 cm) Weight: 21.7 lbs (10 kg)

Mounts and demounts a full range of tires on rim diameters from 4 to 12 inches. Mounts easily to a bench or in any standard, four-position rim-clamp tire changer. A built-in, three fin centering device mounts standard lug-type rims with 2" and larger center hole. Square base prevents turning in the changer during use. Includes a Ken-Tool exclusive, 22" Tire Snake[®] mount/demount tire tool.



Small Tire Changing Tool Part 2



Threadscrew has been milled to fit MTD wheels



