

05

BALANCING & BEAD TOOLS



BALANCING BEADS

Complete wheel end balancing

Ken-Tool Balancing Beads have you covered from motorcycle, passenger, light truck, off-road and class 5-8 vehicles. Our easy-to-use drop in bag saves time and money on new tire installation and can be injected through the valve stem to completely balance the axle end on existing vehicles without dismounting the tire and wheel. Memory technology keeps the beads stabilized, providing a completely balanced axle end in all wheel positions. Ken-Tool Balancing Beads balance the complete axle end...the tire, the wheel and all the moving components of the wheel assembly. TPMS compatible.



LEAD FREE,
ENVIRONMENTALLY
FRIENDLY



EASY TO USE,
DROP IN BAG OR
INSTALL THROUGH
VALVE STEM



SPECIALY
COATED KEN-TOOL
BALANCING BEADS
REPEL MOISTURE
AND AVOID
CLUMPING

Item No.	Description	Amount
31600	Bead Injection Tool for easy installation into the valve stem	
31601	1 oz bags	Case of 160
31602	2 oz bags	Case of 128
31603	3 oz bags	Case of 96
31604	4 oz bags	Case of 92
31606	6 oz bags	Case of 64
31608	8 oz bags	Case of 52
31610	10 oz bags	Case of 40
31612	12 oz bags	Case of 36
31614	14 oz bags	Case of 32
31616	16 oz bags	Case of 28

05 BALANCING & BEAD TOOLS



PNEUMATIC BEAD EXPANDERS

Expansores neumáticos de llantas
Tubes d'extension de talon pneumatiques

Expanders fit most bias ply tubeless tires. A pliable neoprene rubber tube is encased in a tough, long-lasting nylon cover. Expanders slip easily over tire and withstand contact with oil, grease, solvents, and acids. Expands passenger and light truck beads by compressing tread. **T131** is for smaller tires, **T132** for belted bias ply tires and steel belted radials, and **T133** for standard bias ply tires. All models feature an over-pressure relief valve and external pressure quick release valve for safe operation.

Model No.	Item No.	Min/Max Tire OD	Tube Diameter	Weight
A	T131	10 - 22" (26 - 56 cm)	2-1/4" (6 cm)	2 lbs (.9 kg)
	T132	24 - 34" (61 - 86 cm)	2-1/4" (6 cm)	2.8 lbs (1.3 kg)
	T133	22 - 32" (60 - 81 cm)	3/4" (2 cm)	.75 lbs (.3 kg)
	T134	13 - 26" (33 - 70 cm)	2-1/4" (6 cm)	2.7 lbs (1.2 kg)



TIRE BEAD SEATERS

Calzador para llantas
Cordons de talon de pneus

One-piece rubber tube for mounting hard-to-seat radial, bias-belted, or conventional truck tires. As tire is inflated, the lubricated bead seater forms a seal between the rim and tire, allowing the air pressure to force the beads into the rim flange. As proper pressure is reached, the bead seater slides out and over the rim. Use bead lubricant with bead seaters.

Item No.	Fits Rim Sizes	Weight	
Passenger / Light Truck (Camión liviana/vehículo de pasajeros / Automobile/camion léger)			
31446	14-15" (36 - 38 cm)	1.5 lbs (.7 kg)	
Truck (Camión Camion)			
D	31437	16-1/2" to 17-1/2" (42 to 45 cm)	2 lbs (.9 kg)
	31438	19-1/2" (50 cm)	2.3 lbs (1 kg)
	31439	22-1/2" to 24-1/2" (57 to 62 cm)	2.3 lbs (1 kg)



BEAD SEATING TOOL

Outil de portée de talon
Herramienta para calzado de talone

Used on Auto, ATV, and Truck Tires. Designed for use on tires up to 24-1/2 diameter. Digital air pressure gauge and safety release valve included for operator convenience and safety. Plastic nose clip protects chrome and alloy wheels; replacements available.

Item No.	Description	Dimensions	Weight	
B	31444	Steel	25 1/2" x 16 1/2" x 11 1/2" (648 X 419 x 292 mm)	26 lbs / 12 kg
C	31445	Aluminum	25 1/2" x 17" x 11 1/2" (648 X 431 x 292 mm)	11 lbs / 5 kg



EASY-LIFT™ BEAD SEATING STAND

Soporte para calzado de talón Easy-Lift™
Poste de portée de talon Easy-Lift™

Safety First! ERGONOMIC: Reduces back strain while handling 22.5" tubeless tire & wheel assemblies. Aligns beads concentrically on wheel for improved ride & longer tire life. Portable for field service, or can be bolted to the floor. Made of high grade steel. Length: 24" high x 26" wide x 27" long. **PATENTED.**

Model No.	Item No.	Description	Weight
T116	36016	Standard Crown for 8-3/4" diameter hubs	36 lbs (16.4 kg)
T117	36017	Large Crown for 11" Euro hubs	37 lbs (16.8 kg)




EasyLift™
Bead Seating Stand



BEAD SEATING TOOL 36030

Outil de portée de talon
Herramienta para calzado de talone

The Ken-Tool C-Beast lifts the weight of the wheel off the bottom area of the bead of a standing tire/wheel assembly, in order to easily ensure the concentric seating of the bead on a standing Super Single assembly.



Specially designed for use with most super single tires.



WHITE TIRE PASTE 35848

Lubricante Blanco Paste Lube
Lubrifiant Blanc Paste Lube

Premium tire mounting/demounting lubricant dries tacky to prevent rim slippage, with rust retardant.

8 lb. (3.6 kg)