13800

DIGITAL THERMOMETER

Foldout stainless steel probe

• Large, easy-to-read display

AUTOMOTIVE DIGITAL

• Min/Max

13803

• -58°F to 572°F

MULTIMETER

13801

IP54 INFRARED THERMOMETER

- IP54 Splash proof certification
- Magnetic mount for hands-free use • 12:1 distance/spot ratio • Min/Max, diff and lock
 - Backlit display
 - -76°F to 1022°F

inductive pick-up

13809

• Limited Lifetime Warranty

BASIC CATILI DMM

• DC and AC Voltage to 600V

• Preform basic voltage and

resistance measurement

• 2M ohm resistance

10A DC Current

13804

CAT IV DIGITAL MULTIMETER



- ACV/DCV, ACA/DCA, resistance, diode, • Cat IV 600/Cat III 1000V for HEV work frequency, continuity, temperature • High accuracy standard DMM
- Duty cycle and dwell reading • Fuel injector pulse width testing • RPM measurements with included
- RPM measurement
- Ruggedized design
- Inductive pickup/carrying case/ thermocouple probe/test leads

13808

CAT IV CLAMP METER



- DC and AC clamp-on current measurement to 600A
- 1000V DC/ 750V AC voltage ranges
- Cat IV Rated for HEV diagnostics
- High resolution (0.01A), full function clamp meter
- Check starter or charging current Check voltage drops, capturing
- minimum or maximum values

REPLACEMENT PARTS





 Pouch for 13802



for 13803 and 13804

- Protective case for 13803 and 13804
- Temperature adapter for 13803
- K-type thermocouple probe for 13803 and 13804
- Universal hanger & magnet for 13084 Adjustable strap

13915

HANGER **& MAGNET**

UNIVERSAL

FEATURES

- Used for testing electrical circuits in cars, trailers, boats and more
- Retractable test leads pull out and stay at desired length and rewind into its own protective case when not in use
- 18 gauge copper wire with insulated alligator clips
- Different color wires for easy identification
- Maximum amperage: 10 AMPS fully unwound, 6 AMPS wound

1129

RETRACTABLE TEST LEADS - 3 LEADS X 10 FT.



EST LEADS

1130

1138

1137

RETRACTABLE TEST LEADS - 2 LEADS X 30-FT.



1175

RETRACTABLE TEST LEADS -2 LEADS X 15 FT. WITH **BANANA PLUGS**



TEST LEAD SET

REPLACEMENT PARTS

1167R

REPLACEMENT **ALLIGATOR CLIPS** FOR 1176



1170R



















sided carrying case 13810 **VOLT METER**

13802

• UV worklight

Backlit display

• -58°F to 1200°F

13805

Max value capture

• 12:1 distance/spot ratio

DIGITAL STORAGE

• Full auto signal capture

OSCILLOSCOPE/GMM

LANC

• Two- Channel, 20 Mega-sample/second sample rate

· Preset standard sensor/actuator/ignition waveforms

INFRARED THERMOMETER



- Wireless High Amps, Low Amps, and Voltage in one complete kit
- View readings remote on your smartphone or tablet
- mA resolution for parasitic current drain

TEMPERATURE

13914

PROBE

- High current clamp for starter and charging current
- DC /AC Volts for checking voltage drops while under load
- Cat IV rated safety for use with HEV diagnostics

• Audible continuity for checking switches and fuses Cat III 600V safety rating











13912

 Test leads for 13803 and 13804







42

ground lead extension, standard tips, back-probe tips, alligator tips, capacitive pick-up, inductive (triggering) pick-up, AC Adapter, soft-

CAT IV WIRELESS CLAMP/

Glitch mode to capture single events

Complete kit with two shielded test leads,







1140

MAGNETIC RETRACTABLE TEST LEADS - 2 LEADS X 30-FT.

RETRACTABLE TEST LEADS - 2 LEADS X 10 FT.



• Use with any multimeters with steel banana jack connectors

Includes: One 2 x 15-ft. test lead with banana plugs (1175), one pair of test probes (1170R), one pair of alligator clips (1167R), and one pair of spring hooks (1173R)

1173R

REPLACEMENT **SPRING HOOKS** FOR 1176



1174R

REPLACEMENT SET -ALLIGATOR CLIPS, TEST PROBES & SPRING HOOKS



www.langtools.com