## **Workforce® Telescoping and Extended Blow Guns**

Blow Guns featuring our telescoping extension improves reach without refitting the gun. Maximum inlet air pressure: 110 psi.

Part No.	Inlet FNPT	Overall Length	Nozzle	Max. dBA	Air Consumption (SCFM)	Body Material	Retail Pkg				
AG2-10*	1/4 in.	12.5 in. to 17.5 in.	Rubber	87	13	ABS	•				
AG4-10*	1/4 in.	12.5 in.	Rubber	87	13	ABS	•				
AGKIT**	1/4 in.	12.5 in. to 17.5 in.	Rubber	87	13	ABS	•				
*U.S. Pat. No. D562,661 S and 6,698,672 B1											
**U.S. Pat. No. D562,661 S, 6,698,672 B1 and 6,561,233 B2											









#### AGKIT - 6-Piece Blow Gun Kit

This modular kit features an ergonomic blow gun handle that allows 3 specialized extensions to be connected with ease.

#### Inflators

Ideal for inflating air mattresses and sports equipment.

#### Car/Truck Tire Inflator

This tire inflator nozzle, with dual air chuck, has a unique design that allows for the purging of moisture from air lines prior to inflating tires. Doubles as a blow gun. Simply pull the trigger on handle for a steady stream of air.

### 360° Adjustable Blow Gun Nozzle

Adjustable length blow gun nozzle rotates a full 360° and locks at any length between 6.5 and 11 in., making it ideal for tight or hard-to-reach spaces. Includes a threaded removable rubber tip.

# **Workforce® Lever Blow Guns**

Lever-trigger blow guns for most frequent-use applications. Can be disassembled for cleaning or repair using common o-rings.















Part No.	Inlet FNPT	Outlet NPSM Female	Overall Length	Nozzle (see below for nozzle reference chart)	Max. dBA	Air Consumption (SCFM)	Color	Retail Packaging				
Plated Zir	Plated Zinc (Maximum inlet air pressure: 150 psi)											
AG7	1/4 in.	1/8 in.	5 in.	Standard Rubber	87	11	Chrome	•				
AG9-X	1/4 in.	1/8 in.	4.25 in.	Standard Self-Relieving, Safety	87	11	Chrome	-				
AG206	1/4 in.	*	4.5 in.	Self-Relieving, Tamper Resistant, Safety	87	8	Chrome	•				
AG218	1/4 in.	1/8 in.	5.25	High Flow, Safety	87	11	Chrome	•				
Electroplated Die-cast Aluminum (Maximum inlet air pressure: 150 psi)												
AG7B	1/4 in.	1/8 in.	5 in.	Standard Rubber	87	11	Green	•				
AG7C	1/4 in.	1/8 in.	5 in.	Standard Rubber	87	11	Blue	•				
AG7D	1/4 in.	1/8 in.	5 in.	Standard Rubber	87	11	Red	•				
* AG206	* AG206 tip is designed to be non-removable, there is no tip interchange.											