

Levelwind™ Retractable Hose Reels

Levelwind™ Technology - This unique winding system automatically layers the hose back and forth across the reel ensuring that the hose is coiled smoothly, easily...every time. Levelwind reels include hose and lead-in hose.



L8305

FEATURES:

- **Latching Mode Switch** - Choose from latching hose every 3 ft. for extended use or switch to free run for immediate automatic rewinding
- **Seven Position Locking Bracket** - These reels can swivel freely on the mounting bracket up to 135° or can be locked into place using the locking brace. Up to seven different locking angles can be utilized (L8300-W)
- **Adjustable Hose Stopper** - Increase or decrease the length of the hose that remains when the hose is fully retracted
- **Extra Large Swivel** - A 3/4 in. swivel reduces flow restrictions and allows for maximum flow
- **Freestanding Base** - Portable - Use freestanding or mounted on wall or ceiling. Flat base allows reel to rest on ground
- **Built-In Handle** - For carrying ease
- **Durable Construction** - Made from durable UV stabilized polypropylene
- **Hoses Included** - PVC or reinforced rubber twin hose and lead-in hose included
- **Assembled in USA of US and global components**

Levelwind™ Retractable Hose Reels (continued)

Part No.	Application	Hose I.D.	Hose Length	Hose Material	Working Pressure @ 70°F	Temperature Range (F°)	Hose Inlet	Hose Outlet	Weight	Retail Pkg
L8305	Air	3/8 in.	50 ft.	PVC	350 psi	15° to 150°	3/4 in.-11½ Male GHT	1/4 in. MNPT	24 lbs.	●
L8306	Air	3/8 in.	75 ft.	PVC	350 psi	15° to 150°	3/4 in.-11½ Male GHT	1/4 in. MNPT	30 lbs.	●
L8310	Air	3/8 in.	100 ft.	PVC	350 psi	15° to 150°	3/4 in.-11½ Male GHT	1/4 in. MNPT	31 lbs.	●
L8335*	Air/Water	1/2 in.	50 ft.	PVC	300 psi	15° to 150°	3/4 in.-11½ Male GHT	1/2 in. MNPT	27 lbs.	●
L8344	Garden	5/8 in.	60 ft.	PVC	140 psi	40° to 140°	3/4 in.-11½ Male GHT	3/4 in.-11½ Male GHT	31 lbs.	●
L8345	Garden	1/2 in.	75 ft.	PVC	140 psi	40° to 140°	3/4 in.-11½ Male GHT	3/4 in.-11½ Male GHT	29 lbs.	●
L8346	Garden	5/8 in.	50 ft.	PVC	140 psi	40° to 140°	3/4 in.-11½ Male GHT	3/4 in.-11½ Male GHT	25 lbs.	●
L8349**	Cold Water Washdown	5/8 in.	50 ft.	PVC	140 psi	40° to 140°	3/4 in.-11½ Male GHT	3/4 in.-11½ Male GHT	24 lbs.	-
L8350	Potable Water	1/2 in.	75 ft.	PVC	140 psi	40° to 140°	3/4 in.-11½ Male GHT	3/4 in.-11½ Male GHT	28 lbs.	-

*Garden hose adapters included for discharge and lead-in hoses

**Model L8349 is designed for safe water drinking/food service applications



L8344



L8305



L8344 Retail Package



L8305 Retail Package