

## LT999 SAE Thread Chaser Socket Kit

**NEW PRODUCT**

Recondition threads on SAE high pressure male/female fittings. Hollow end tap slides over flared end of line for easy re-threading female connector. Compact design with pass through bored out center hole on each socket. Allows thread reconditioning with flared tip supply line inside pressure fitting. Ideal for gas, AC, and liquid high pressure fittings common in heavy equipment, trucking, marine and aircraft industries. Easy hand operation with supplied handle.

INCLUDES SIZES:

5/8" - 18UNF  
3/4" - 16UNF  
7/8" - 14UNF  
1" - 14UNF  
1-1/16" - 14UNF



LT999-5  
up close



## LT995 Timing Gear Pliers

The LT995 will allow mechanic to turn timing gear when timing belt adjustment is needed. Aids in removal and replacement of timing gears and serpentine belt pulleys. Includes 6 sets of interchangeable composite inserts which safely grip timing gear teeth. **Each composite insert now mounts and swivels on 2 pins located on the head of wrench for a secure fit and greater grip.** Performs timing gear removal by preventing rotation of timing gear sprocket while retaining nut or bolt are removed. Prevents camshaft rotation during timing gear removal eliminating valve/piston interference and subsequent damage. Securely grips all serpentine belt pulleys. US Patent No. 7,077,036B1.



## LT740 Funnel Lok™

The Funnel Lok™ hands-free funnel holder is a simple, yet revolutionary tool designed to hold any standard-size funnel firmly in place--making it easy to transfer gasoline, oil, coolant, or any other fluids and powders without slipping or spilling. Provides a stable "third hand". Shaped like a pair of pliers with spring torque action, the Funnel Lok™ features four stabilizing prongs that can be inserted into any container or tank opening from 1 1/4" to 2 1/4" in size. This creates a steady base for the funnel to be held securely in place by the adjustable rings. Made of durable ABS material. Allows the air to vent, which eliminates the risk of blow back. It not only prevents spills of potentially hazardous chemicals, but its hands-free design allows containers to fully drain.



## LT940 Gas Tank Fuel Pump Removal Tool

This tool removes plastic fuel pump retaining rings. Universal adjustable design fits most plastic retaining rings. **Increased length of ears and slots in ears allow for wider application for more secure fit when grabbing teeth around fuel pump retaining rings.** Prevents damage to original retaining ring. Use with a 1/2" drive extension and ratchet. Use to re-install old retaining ring.



## PAINT & BODY

### LT-800 Inflatable Dent Remover - 2 pieces

The LT-800 Inflatable Dent Remover uses hand pumped air pressure to push dents out from the inside of door and fender panels. Comes in 2 sizes: The LT-805 (8" x 8" Square Inflatable Dent Remover) is for removing dents in tight corners or along welded seams and panel edges. The LT-810 (14" x 8" Oblong Inflatable Dent Remover) is for longer more accessible large dents. Each bag has 5 feet of air hose with oversize hand pump bulb for long reach. Perfect for paintless auto body repair. Universal applications for all automotive and truck door and body panel repair. Eliminate high points caused by body slide hammers and picks. Pushes dents out to their normal shape eliminating excessive bondo and sanding work. A real material and time saver.

