



## HR5000



### 2" ROTARY HAMMER Air Cushion Design for Hard Hitting Action

- All ball-and-needle bearing construction for longer tool life
- Powerful 11 AMP motor for the most demanding applications
- Built-in clutch reduces gear damage by disengaging gears if the bit binds
- 2-mode operation for "Hammering Only" or "Hammering with Rotation" for multiple applications
- Sequential impact timing delivers timed hammering during rotation to minimize overlapping bit impacts resulting in up to 50% faster drilling

**Model HR5000 Includes:** Hex Wrench (783202-0), Hex Wrench (783203-8), Wrench (783204-6), Tool Case

## HR4041C



### 1-9/16" ROTARY HAMMER Electronic Controller for Operator Convenience

- Powerful 12 AMP motor delivers 6.8 ft.lbs. of impact energy
- Constant speed control automatically applies additional power to the motor to maintain speed under load
- Soft start suppresses start-up reaction for increased accuracy
- Variable speed control dial enables user to match the speed to the application
- "No hammering while idling" helps increase tool life.
- Torque limiting clutch engineered to prevent gear damage by automatically disengaging gears

**Model HR4041C Includes:** Depth Gauge (321248-4), Side Handle (416549-4), Tool Case



## HR3210C



### 1-1/4" AVT® ROTARY HAMMER Anti-Vibration Technology for 2X Less Vibration

- Powerful 8.2 AMP motor delivers 4.7 ft.lbs. of impact energy
- Constant speed control automatically applies additional power to the motor to maintain speed under load
- Soft start suppresses start-up reaction for more precision and better accuracy
- L.E.D. service light notifies the user approximately 8 hours before the brushes need to be replaced
- L.E.D. power light indicates switch failure or cord damage

**Model HR3210C Includes:** Side Handle (151769-0), Depth Gauge (321248-4), Hammer Bit Grease (194683-7), Tool Case

## HR2811F



### 1-1/8" ROTARY HAMMER Torque Limiting Clutch Engineered to Prevent Gear Damage

- Powerful 7.0 AMP motor delivers 2.1 ft.lbs. of impact energy
- L.E.D. light illuminates drilling surface for more productivity in low light applications
- 3-mode operation for "Rotation Only", "Hammering with Rotation" or "Hammering Only"
- "No hammering when idling" function helps increase tool life
- Ergonomic "D-shaped" handle with rubberized soft grip for increased comfort

**Model HR2811F Includes:** Depth Gauge (324219-0), Side Handle (154842-5), Tool Case

AMPS	11
Capacities: Concrete Drilling	2"
Concrete Drilling w/ Core Bit	5-7/8"
Impact Energy	11.8 J / 8.7 ft.lbs.
Vibration (m/s <sup>2</sup> )	25
Blows Per Minute	2,100 BPM
No Load Speed	260 RPM
Overall Length	18-3/4"
Cord Length (ft)	8.2'
Net Weight	21.8 lbs.
Shipping Weight	35 lbs.
Bit Type	Accepts Spline shank

AMPS	12
Capacities: Concrete Drilling	1-9/16"
Concrete Drilling w/ Core Bit	4-5/8"
Impact Energy	9.2 J / 6.8 ft.lbs.
Vibration (m/s <sup>2</sup> )	15
Blows Per Minute (variable speed)	1,300 - 2,600 BPM
No Load Speed (variable speed)	230 - 460 RPM
Overall Length	16-7/8"
Cord Length (ft)	16.4'
Net Weight	14.8 lbs.
Shipping Weight	20.3 lbs.
Bit Type	Accepts Spline shank

AMPS	8.2
Capacities: Concrete Drilling	1-1/4"
Concrete Drilling w/ Core Bit	3-1/2"
Impact Energy	5.5 J / 4.1 ft.lbs.
Vibration (m/s <sup>2</sup> )	10
Blows Per Minute (variable speed)	1,650 - 3,300 BPM
No Load Speed (variable speed)	315 - 630 RPM
Overall Length	15-5/8"
Cord Length (ft)	16.4'
Net Weight	11.4 lbs.
Shipping Weight	19.84 lbs.
Bit Type	Accepts SDS-PLUS

AMPS	7
Capacities: Concrete Drilling	1-1/8"
Concrete Drilling w/ Core Bit	3-1/8"
Impact Energy	2.9 J / 2.1
Vibration (m/s <sup>2</sup> )	15
Blows Per Minute (variable speed)	0 - 4,500 BPM
No Load Speed (variable speed)	0 - 1,100 RPM
Overall Length	12-5/8"
Cord Length (ft)	8.2'
Net Weight	7.7 lbs.
Shipping Weight	11.8 lbs.
Bit Type	Accepts SDS-PLUS



## HR2641



### 1" AVT® ROTARY HAMMER Anti-Vibration Technology for 2X Less Vibration

- Powerful 8 AMP motor delivers 2.1 ft.lbs./2.9 J. of impact energy
- Anti-Vibration Technology (AVT®) is an internal counterbalance system and impact bolt damper spring that greatly reduces vibration
- Torque limiting clutch engineered to prevent gear damage
- Recessed 3-mode function selector is located below gear housing for improved durability
- Retractable tool hook secures the tool when not in use

**Model HR2641 Includes:** Handle, LXF01CW (451749-9), Depth Gauge, HR2611F, HR2621 (331886-4), Tool Case

## HR2475



### 1" ROTARY HAMMER Torque Limiting Clutch Engineered to Prevent Gear Damage

- Powerful 7.0 AMP motor delivers 2 ft.lbs. of impact energy
- 3-mode operation for "Rotation Only", "Hammering with Rotation" or "Hammering Only"
- Variable speed trigger enables user to match the speed to the application for greater versatility
- Ergonomic "D-shaped" handle with rubberized soft grip for increased comfort
- One-touch sliding chuck for quick bit changes

**Model HR2475 Includes:** Side Handle (158057-6), Depth Gauge (324219-0), Tool Case

## HR2611F



### 1" AVT® ROTARY HAMMER, ACCEPTS SDS-PLUS Anti-Vibration Technology for 2X Less Vibration

- Powerful 7 AMP motor delivers 2.1 ft.lbs. of impact energy to handle the most demanding applications
- Anti-Vibration Technology (AVT®) is an internal counterbalance system that greatly reduces vibration
- Integrated damper spring at the base of the impact bolt is engineered to absorb impact vibrations from the drill bit
- L.E.D. light illuminates drilling surface for more productivity in low light applications
- Recessed hammer function selector located below gear housing for improved durability

**Model HR2611F Includes:** Handle, LXF01CW (451749-9), Depth Gauge, HR2611F, HR2621 (331886-4), Tool Case

## HR1830F



### 11/16" ROTARY HAMMER Compact with Less Weight (4.2 lbs.)

- Powerful 4.2 AMP motor delivers .9 ft.lbs. of impact energy
- L.E.D. light illuminates drilling surface for more productivity in low light applications
- Torque limiting clutch engineered to prevent gear damage
- 2-mode operation for "Rotation Only", "Hammering with Rotation"
- One-touch sliding chuck for quick bit changes

**Model HR1830F Includes:** Depth Gauge (415486-9), Side Handle (154842-5), Tool Case

AMPS	8
Capacities: Concrete Drilling	1"
Concrete Drilling w/ Core Bit	3-1/8"
Impact Energy	2.9 J / 2.1 ft.lbs.
Vibration (m/s <sup>2</sup> )	11.5
Blows Per Minute (variable speed)	0 - 4,500 BPM
No Load Speed (variable speed)	0 - 1,100 RPM
Overall Length	16-5/8"
Cord Length (ft)	13.1'
Net Weight	7.1 lbs.
Shipping Weight	11.55 lbs.
Bit Type	Accepts SDS-PLUS

AMPS	7
Capacities: Concrete Drilling	1"
Concrete Drilling w/ Core Bit	3-1/8"
Impact Energy	2.7 J / 2
Vibration (m/s <sup>2</sup> )	15.5
Blows Per Minute (variable speed)	0 - 4,500 BPM
No Load Speed (variable speed)	0 - 1,100 RPM
Overall Length	16-7/8"
Cord Length (ft)	13.1'
Net Weight	6.6 lbs.
Shipping Weight	11.9 lbs.
Bit Type	Accepts SDS-PLUS

AMPS	7
Capacities: Concrete Drilling	1"
Concrete Drilling w/ Core Bit	2-11/16"
Impact Energy	2.9 J / 2.1 ft.lbs.
Vibration (m/s <sup>2</sup> )	11.5
Blows Per Minute (variable speed)	0 - 4,600 BPM
No Load Speed (variable speed)	0 - 1,200 RPM
Overall Length	15-1/8"
Cord Length (ft)	13.1'
Net Weight	6.6 lbs.
Shipping Weight	11.7 lbs.
Bit Type	Accepts SDS-PLUS

AMPS	4.2
Capacities: Concrete Drilling	11/16"
Concrete Drilling w/ Core Bit	
Impact Energy	1.2 J, .9 ft.lbs.
Vibration (m/s <sup>2</sup> )	14
Blows Per Minute (variable speed)	0 - 5,000 BPM
No Load Speed (variable speed)	0 - 1,500 RPM
Overall Length	10-7/8"
Cord Length (ft)	8.2'
Net Weight	4.2 lbs.
Shipping Weight	11 lbs.
Bit Type	Accepts SDS-PLUS