



JS8000

FIBER CEMENT SHEAR

Cuts Quickly While Producing Less Dust

- Single-piece shear head is machined from precisely milled aluminum to ensure blades cut straight
- Solid steel blades cut clean, straight lines with a maximum cutting capacity up to 5/16"
- 1/2" protected spindle withstands heavy torque loads
- Lightweight cast aluminum gear housing for durability
- Retractable tool hook allows user to work in tight spaces

Model JS8000 Includes: Shear Blade, Center (725129-8), (2) Shear Blade, Side (725130-3), Hex Wrench (783221-6), Tool Case (824780-2)

Capacity	5/16"
Strokes Per Minute (variable speed)	0 - 2,500 SPM
AMPS	6.5
Overall Length	13-5/8"
Net Weight	4.8 lbs.
Shipping Weight	8.5 lbs.



JN3201

10 GAUGE NIBBLER

Powerful 6.2 AMP Motor; 1,300 SPM for the Most Demanding Applications

- Less noise at 81 dB(A) for continuous operation
- Well balanced with a rubberized soft grip handle for greater comfort
- Built-in thickness gauge for added convenience
- Refined design at only 7.4 lbs.
- Lock-on switch for continuous operation

Model JN3201 Includes: Punch (792728-1), Die (792292-2), Hex Wrench (783201-2), Spanner Wrench (781019-5)

Capacities:	Aluminum Mild Steel Stainless	10 ga. (mm) 10 ga. (mm) 13 ga. (mm)
Strokes Per Minute		1,300 SPM
Cutting Radius:	Inner Edge Outer Edge	4-3/4" 5-1/16"
AMPS		6.2
Overall Length		8-1/2"
Net Weight		7.5 lbs.
Shipping Weight		8.8 lbs.



JN1601

16 GAUGE NIBBLER

Handles 16 Ga. Mild Steel and 18 Ga. Stainless

- For clean and precise work in keystone plate, deck plate and other sheet materials
- Slim and ergonomic body design for easy gripping
- Die rotates 360°; large 1/4" stroke
- Extremely light (weighs only 3.6 lbs.) for easier handling
- Lock-on sliding switch for continuous use
- Built-in thickness gauge for convenience

Model JN1601 Includes: Spanner Wrench (781028-4), Blade Wrench (783208-8)

Capacities:	Aluminum Mild Steel Stainless	10 ga. (mm) 16 ga. (mm) 18 ga. (mm)
Strokes Per Minute		2,200 SPM
Cutting Radius:	Inner Edge Outer Edge	1-3/4" 2"
AMPS		5
Overall Length		10-1/4"
Net Weight		3.6 lbs.
Shipping Weight		5.28 lbs.



3.0Ah BATTERY
XNJ01Z



XNJ01

18v LXT® 16 GAUGE NIBBLER KIT

Powerful, Versatile and Cordless

- Makita-built motor delivers 1,900 SPM for fast and smooth cutting
- Ideal for cutting roofing sheet metal at thicknesses up to 16 gauge
- Die holder rotates 360° to meet demands of cutting direction
- Convenient chip disposal is below cutting material to minimize damage to cutting surface
- Cutting radius: inner edge 1-3/4"; outer edge 2"

Model XNJ01 Includes: (2) 18V LXT® Lithium-Ion 3.0Ah Battery (BL1830), 18V Lithium-Ion Rapid Optimum Charger (DC18RC), Punch (A-83951), Spanner Wrench (781028-4), Tool Bag

Model XNJ01Z Includes: Tool Only; Battery and Charger not included

Capacities:	Aluminum Mild Steel Stainless	12 ga. (mm) 16 ga. (mm) 18 ga. (mm)
Strokes Per Minute (variable speed)		0 - 1,900 SPM
Cutting Radius:	Inner Edge Outer Edge	1-3/4" 2"
Battery		18V LXT® Lithium-Ion
Overall Length		12-3/8"
Net Weight (with battery)		4.8 lbs.
Shipping Weight		13.3 lbs.



JS1300

18 GAUGE STRAIGHT SHEAR

Powerful 6.5 AMP Motor for Continuous Operation

- Cuts up to 18 gauge mild steel, 20 gauge stainless and 13 gauge aluminum
- Pistol grip design for comfort and convenience
- Shear head attachment rotates 360°
- Large variable speed trigger switch for controlled cutting speed
- Retractable belt clip allows operation in tight areas
- Lock-on button for continuous operation

Model JS1300 Includes: Shear Blade, Right (725092-5), Shear Blade, Left (725093-3), Shear Blade, Center (725094-1), Shear Head Assembly (125112-9), Hex Wrench (783215-1)

Capacities:	Aluminum Mild Steel Stainless	13 ga. (mm) 18 ga. (mm) 20 ga. (mm)
Strokes Per Minute (variable speed)		0 - 2,500 SPM
AMPS		6.5
Overall Length		11-7/8"
Net Weight		3.9 lbs.
Shipping Weight		5.28 lbs.



3.0Ah BATTERY
XSJ01Z



XSJ01

18v LXT® 18 GAUGE STRAIGHT SHEAR KIT

Swivel Shear Head Rotates 360°

- Makita-built 4-pole motor delivers 3,000 strokes per minute for faster cutting
- Cuts up to 18 gauge mild steel and 20 gauge stainless steel
- Weighs only 5.3 lbs. with battery for reduced operator fatigue
- Reversible belt-clip attaches to either side of the tool
- Rubberized soft grip handle provides increased comfort on the job

Model XSJ01 Includes: (2) 18V LXT® Lithium-Ion 3.0Ah Battery (BL1830), 18V Lithium-Ion Rapid Optimum Charger (DC18RC), Tool Bag

Model XSJ01Z Includes: Tool Only; Battery and Charger not included

Capacities:	Mild Steel Stainless	18 ga. (mm) 20 ga. (mm)
Strokes Per Minute		3,000 SPM
Battery		18V LXT® Lithium-Ion
Overall Length		13-3/4"
Net Weight (with battery)		5.3 lbs.
Shipping Weight		14 lbs.



JS1602

16 GAUGE SHEAR

Cuts 16 Ga. Mild Steel and 18 Ga. Stainless

- Powerful 3.3 AMP motor delivers 4,000 SPM for the most demanding applications
- Small circumference barrel grip (only 2-1/4") for added comfort
- Refined design at only 3.4 lbs. for increased control
- Lock-on slide switch for continuous operation
- Built-in thickness gauge for added convenience
- Large easily replaceable blades with 8 cutting edge each

Model JS1602 Includes: Hex Wrench (783201-2), Shear Blade Set (191383-0)

Capacities:	Aluminum Mild Steel Stainless	13 ga. (mm) 16 ga. (mm) 18 ga. (mm)
Strokes Per Minute		4,000 SPM
Cutting Radius		1-3/16"
AMPS		3.3
Overall Length		12-1/2"
Net Weight		3.4 lbs.
Shipping Weight		4.9 lbs.



JS3201

10 GAUGE SHEAR

Powerful 6.2 AMP Motor; 1,600 SPM for the Most Demanding Applications

- Less noise at 81 dB(A) for continuous operation
- Tight 2" cutting radius for greater versatility
- Lock-on switch for continuous operation
- Built-in thickness gauge for convenience
- Refined design at only 7.4 lbs. for increased control
- Large, easily replaceable blades with 8 cutting edges each

Model JS3201 Includes: Hex Wrench (783202-0), Shear Blade Set, JS3201 (792287-5), Thickness Gauge (123456)

Capacities:	Aluminum Mild Steel Stainless	9 ga. (mm) 10 ga. (mm) 13 ga. (mm)
Strokes Per Min.		1,600
Cutting Radius		2"
AMPS		6.2
Overall Length		8-3/8"
Net Weight		7.4 lbs.
Shipping Weight		8.8 lbs.