PORTABLE & POWERFUL



XSL02Z

18v X2 LXT® BRUSHLESS 7-1/2" COMPOUND MITER SAW

Powerful BL™ Brushless Motor Delivers 5,700 RPM for Faster Cutting

- Two 18V LXT® Lithium-Ion Batteries deliver the power and performance of a corded miter saw without leaving the 18V LXT® platform
- Automatic Speed Change[™] technology adjusts cutting speed and torque during cut for optimum performance
- The BL™ Brushless Motor eliminates carbon brushes, enabling the BL Motor to run cooler and more efficiently for longer life
- Efficient BL™ Brushless motor is electronically controlled to optimize battery energy use for up to 50% longer run time per charge

Tool only - battery and charger not included

Model XSL02Z Includes: 7-1/2" 40T C.T. Miter Saw Blade

(A-90912); Battery and Charger not included

| Blade Diameter | 7-1/2" |
|--|-------------------------|
| Arbor | 5/8" |
| Max. Cutting Capacity (Bevel/Miter): 90°/90° (2-1/16" x 11-3/4"), 45°/45° (2-1/16" x 8-3/8") | |
| No Load Speed | 5,700 RPM |
| Battery | 2X 18V LXT® Lithium-Ion |
| Dimensions (LxWxH) | 25-3/4" x 17" x 17-1/2" |
| Net Weight (with battery) | 28.9 lbs. |
| Shipping Weight | 38 lbs. |
| | |



XSL01

18v LXT® 7-1/2" COMPOUND MITER SAW KIT

Large Cutting Capacity up to 2-1/16" and 11-3/4" Crosscuts at 90°

- Powerful Makita-built motor delivers 2,200 RPM
- Weighs only 27.5 lbs. with battery for reduced operator fatigue
 Four steel rail sliding system increases rigidity to
- produce superior accurate cuts
- Miters 0-47° left and 0-57° right; bevels 0-45° left and 0-5° right

Model XSL01 Includes: (2) 18V LXT® Lithium-lon 3.0Ah Battery (BL1830), 18V Lithium-lon Rapid Optimum Charger (DC18RC), 7-1/2" 40T C.T. Miter Saw Blade (A-90912), (2) Extension Wing (322312-4), Vertical Vise (122571-8), Dust Bag (122852-0), Tiangular Rule (762001-3), Socket Wrench (782223-9)

Model XSL01Z Includes: Tool Only; Battery and Charger not included

| Blade Diameter | 7-1/2" |
|--|-------------------------|
| Arbor | 5/8" |
| Max. Cutting Capacity (Bevel/Miter): 90°/90° (2-9/16" x 11-3/4"), 45°/45° (1" x 11-3/4") | |
| No Load Speed | 2,200 RPM |
| Battery | 18V LXT® Lithium-Ion |
| Dimensions (LxWxH) | 25-3/4" x 17" x 17-7/8" |
| Net Weight (with battery) | 27.5 lbs. |
| Shipping Weight | 44 lbs. |



LS0815F

8-1/2" SLIDE COMPOUND MITER SAW

Compact and Lightweight Design for Job Site Portability

- Powerful 10.5 AMP direct drive motor requires less maintenance and delivers 5,000 RPM
- Cuts up to 12" at 90° and 8-1/2" at 45°
- Miters 0°-50° left and 0°-60° right, with positive stops at 0°, 15°, 22.5°, 31.6°, 45° (right or left)
- · Compact and lightweight (31.1 lbs.) for job site portability

Model LS0815F Includes: 8-1/2" 48T Carbide-Tipped Miter Saw Blade (A-95934), Triangle Rule for Miter Saws (JM27000328), Vertical Vise, LS0815F (JM23510009), Dust Bag, LS0815F (JM23510010), Box Wrench, LS0815F (782230-2), (2) Extension Wing (JM23000127)

| Blade Diameter | 8-1/2" |
|--|------------------------------------|
| Arbor | 5/8" |
| Max. Cutting Capacities: at 90° (2-9/16" x 12 | 2"), at 45° L/R (2-9/16" x 8-1/2") |
| No Load Speed | 5,000 RPM |
| Dimensions (LxWxH) | 29-3/4" x 17-3/4" x 19-1/4" |
| Net Weight | 31.1 lbs. |
| Shipping Weight | 41.8 lbs. |
| | |



LS1221

12" COMPOUND MITER SAW Consistently Precise Cutting Performance

• Large cutting capacity (3-7/8" x 6" at 90°)

- 4-1/2" tall pivoting fence for cutting up to 5-1/2" crown molding
- Powerful 15 AMP direct drive motor delivers 4,000 RPM for smooth performance
- Positive stops at 9 settings; 15°, 22.5°, 31.6°, 45° right or left and 0° $\,$
- Horizontal D-handle design for easy and comfortable operation
- Electric brake for maximum productivity

Model LS1221 Includes: 12" x 1" 40T Micro-Polished Miter Saw Blade (A-93706), Vertical Vise (122540-9), Extension Wing (323726-0), Socket Wrench (782232-8), Dust Bag (122852-0)

| Blade Diameter | 12" |
|---|---------------------------------|
| Arbor | 5/8" |
| Max. Cutting Capacities: at 90° (3-7/8" x 6" |), at 45° L/R (2-3/4" x 5-7/8") |
| No Load Speed | 4,000 RPM |
| Dimensions (LxWxH) | 24" x 26-1/2" x 23-7/8" |
| Net Weight | 37 lbs. |
| Shipping Weight | 50 lbs. |
| | |



LS1040

10" COMPOUND MITER SAW Pivoting Fence for Supporting

Larger Material

• Powerful 15 AMP direct drive motor for improved performance

- Dual post compound pivoting arm; bevel cuts up to 45° to the left
- · Weighs only 24.2 lbs. for easy portability
- Positive stops at 9 settings: 15°, 22.5°, 30°, 45° right or left & 0° (90° cuts)
- Miter cuts 0 45° left and 0 52° right

Model LS1040 Includes: 10" x 5/8" 40T Micro-Polished Miter Saw Blade (A-93669), Dust Bag (122852-0), Triangular Rule (762001-3), Vertical Vise (122536-0), Socket Wrench (782232-8)

| Blade Diameter | 10" |
|--|-------------------------|
| Arbor | 5/8" |
| Max. Cutting Capacities: at 90° (2-3/4" x 5-1/8"), at 45° L/R (1-3/8" x 3-5/8") | |
| No Load Speed | 4,600 RPM |
| Dimensions (LxWxH) | 20-7/8" x 18-3/4" x 21" |
| Net Weight | 27.3 lbs. |
| Shipping Weight | 28 lbs. |
| | |

Jobsite Miter Saw Stands Fits All Makita® Miter Saws



Large Solid Rubber Wheels for Easier Jobsite Portability

- Material support extensions (extend 9') with adjustable leg supports for increased cutting accuracy
- Spring-loaded mechanism engineered for quick and easy jobsite set up
- Durable duty aluminum feed roller and adjustable material stop engineered for increased speed on repetitive cuts
- Compact design (46" folded) for convenient transportation to and from the jobsite, and easy vertical or horizontal storage
- 2-Position adjustable stand provides additional height set up for increased comfort
- Adjustable non-marring rubberized feet provide additional support when leveling stand on uneven surfaces

| Material Support Extensions | 9 |
|-----------------------------|-------------------------|
| Spring Loading Mechanism | Yes |
| In-Feed Roller | Yes |
| Material Stop | Yes |
| Folded Dimensions (W) | 46' |
| Dimensions (LxWxH) | 46" x 19-3/4" x 15-3/4" |
| Net Weight | 58.0 lbs |
| Shipping Weight | 66.0 lbs |
| | |



Ideal for Jobsite Use

- · Large platform base for additional work space
- 5-position adjustable stand fits different height requirements
 Material support extensions (extends 9') with feed
- roller deliver enhanced convenience and work speed
- · Solid rubber 12" wheels for easy portability, job to job
- · Spring loaded mechanism for quick and easy setups



| Material Support Extensions | 9' |
|-----------------------------|-----------------------------|
| Spring Loading Mechanism | Yes |
| In-Feed Roller | Yes |
| Material Stop | Yes |
| Folded Dimensions (W) | 50-1/2" |
| Dimensions (LxWxH) | 50-1/2" x 21-1/2" x 15-3/4" |
| Net Weight | 79.0 lbs. |
| Shipping Weight | 90.7 lbs. |
| | |