












Only *Martin* Provides This Added Warranty —
If a Hammer Head Should Loosen at Any Time,
Return It for Handle Replacement or a New Hammer.

Type	Description	Part Number		Std. Pkg. Qty.
		Wood handle	Fiberglass Handle	
DINGING HAMMER 	For fender and high-crowned panel dinging or bumping. Both high and low-crown faces for "on or off dolly" work. Faces, 1-1/4" and 1-9/16". Round heads, 6" overall. Weight 1.04 lb	150G	150FG	6
DINGING HAMMER 	For light dinging and long reach. Square face permits dinging close to moulding or beading. Faces, 1-1/4" round, 1-1/16" square head 6" overall. Weight .85 lb	151G	151FG	6
CROSS CHISEL HAMMER 	Excellent for finishing. Cross peen used for working in sharp corners around mouldings and for caulking. Round face — 1-9/16" diameter. Chisel — 3" long. Weight .87 lb	153G	153FG	6
CURVED CROSS CHISEL HAMMER 	Excellent for finishing. Cross peen used for working in sharp corners around mouldings and for caulking. Well balanced curved chisel for work in close places. Round face — 1-9/16" diameter. Chisel — 3" long. Weight .85 lb	153GB	153FGB	6
CROSS CHISEL SHRINKING HAMMER 	Cross grooved. Extra wide faces are cross grooved and used for shrinkage on large surfaces — chisel end used on sharp corners. Flat round face — 1-9/16" diameter. Chisel — 3" long. Weight .87 lb	153S	153SFG	6
VERTICAL CHISEL HAMMER 	Excellent for finishing. Cross peen used for working in sharp corners around mouldings and for caulking. Vertical chisel end used on sharp corners. Round face — 1-1/2" diameter. 5/8" Chisel — 5-1/2" long. Weight .85 lb	—	154FG	6
VERTICAL CHISEL SHRINKING HAMMER 	Cross grooved. Extra wide faces are cross grooved and used for shrinkage on large surfaces — vertical chisel end used on sharp corners. Round face — 1-1/2" diameter. Chisel — 5-1/2" long. Weight .87 lb	—	154SFG	6
FENDER BUMPER 	For bumping where hand and dolly cannot reach. Ample clearance for obstructions. Also used as a caulking iron. Length of head, 8-3/4". Weight 2.8 lb	155G	155FG	4
PICK HAMMER 	Long-reach, thin point for low spot on low-crown panels. Reaches over inner obstructions. One high-crown face. Face, 1-1/4" round point, 1/32" radius. Length of pointed end, 5-1/2". Weight .91 lb	156G	156FG	6
CURVED PICK HAMMER 	Like 156G except pick end is bent in arc of normal blow. Reaches behind reinforcements to difficult spots. Face, 11/4" round point, 1/32" radius. Length of pointed end, 5-1/2". Weight .86 lb	156GB	156FGB	6
GENERAL PURPOSE PICK HAMMER 	Medium size point and reach for general work. Low crown strawberry point for perfect balance. Face, 1-9/16" round point, 3/32" radius. Length of pick end, 3-3/4". Weight .91 lb	158G	158FG	6