

Butane-Powered Soldering Irons

Ultratorch® UT-200 & UT-200Si Ultratips® and Accessories



UT Series
Ultratorch UT-200

2.6 Hour Run Time

UT Series
Ultratorch UT-200Si

2.6 Hour Run Time

Ultratorch UT-200 and UT-200Si

Model No.	Description
UT-200	Butane-powered soldering iron, heat tool and torch with soldering tip, hot air tip, shrink attachment and protective cap
UT-200Si	Self-igniting, butane-powered soldering iron/heat tool, with soldering tip, hot air tip, shrink attachment and protective cap

Specifications

- **Approx. Soldering Tip Temp.:** 482° - 986°F (250° - 530°C)
- **Approx. Hot Air Tip Temp.:** 1004°F (540°C)
- **Approx. Torch Tip Temp.:** UT-200 2372°F (1260°C)
- **Approx. Operating Time:** 120 min.
- **Fuel Tank Capacity:** 2.2 fl. oz. (63 cc)
- **Tool Dimensions:** 11.9" L (300mm)
- **Tool Net Weight:** 9 oz.
- **Tool Kit Weight:** 13.3 oz.
- **Shipping Weight:** 1 lb.
- **Shipped Empty**
-

NOTE: Users should independently evaluate the suitability of the product for their application.




Solder



Desolder



Flameless Heat



Torch (UT-200 only)

Butane-powered Soldering Iron/Heat Tools

UT-200

- Operates as a soldering iron, flameless heat tool and butane torch
- Standard with Ultratip soldering tip, hot air tip, shrink attachment and protective cap
- Equivalent to 200 watt max. electric soldering iron
- Adjustable temperatures up to 2372°F/1260°C
- High power (BTU's) makes it perfect for heavy-duty service and maintenance
- Sturdy metal tank holds enough fuel for 2.6 hours of operation at middle temperature setting
- Use to pinpoint heat, heat shrink tubing, solder and desolder, strip insulation, terminate specialty connectors, torch materials and more
- Refill with Master Ultratane Butane for best performance (**page 31**)
- Optional accessories interchangeable between UT-200 and UT-200Si models

UT-200Si

- Operates as a soldering iron and flameless heat tool
- Self-ignition with push button for fast, easy starting
- Standard with Ultratip soldering tip, hot air tip, shrink attachment, spanner and open end wrenches, and protective cap
- Equivalent to 200 watt max. electric soldering iron
- Adjustable temperatures up to 1004°F/540°C
- High power (BTU's) makes it perfect for heavy-duty service and maintenance
- Sturdy metal tank holds enough fuel for 2.6 hours of operation at middle temperature setting
- Use to pinpoint heat, heat shrink tubing, solder and desolder, strip insulation, terminate specialty connectors, torch materials and more
- Refill with Master Ultratane Butane for best performance (**page 31**)
- Optional accessories interchangeable between UT-200 and UT-200Si models

Butane-Powered Soldering Irons

Ultratorch® UT-200 & UT-200Si Ultratips® and Accessories



72-01-01
3mm dia. tapered needle



72-01-02
10mm dia. chisel



72-01-03
4mm dia. spade



72-01-05
1mm dia. tapered needle



72-01-06
4mm dia. micro spade



72-01-07
1.5mm dia. tapered pyramid



72-01-11
7mm dia. chisel



72-01-12
4mm dia. chisel



72-01-13
12.5mm dia. 45° spade



72-01-14
Adapter



72-01-51
5.6 O.D./3.6 I.D. (mm)



72-01-52
8.6 O.D./6.6 I.D. (mm)



72-01-53
11.5 O.D./9.7 I.D. (mm)



72-02
Protective cap



72-01-54
1 1/25.4mm dia., .1 1/25.4mm wide heat shrink



72-01-55
1.25 1/32mm dia., 1.25 1/32mm wide heat shrink



80-35
Ejector spanner wrench



80-40
Open end wrench



72-52U
Carrying strap

Ultratorch UT-200 & UT-200Si Tips and Accessories

Model No.	Description
Soldering Tips	
72-01-01	3mm dia. tapered needle soldering tip
72-01-02	10mm dia. chisel soldering tip (std. UT-200, UT-200Si)
72-01-03	4mm dia. spade soldering tip
72-01-05	1mm dia. tapered needle soldering tip
72-01-06	4mm dia. micro spade soldering tip
72-01-11	7mm dia. chisel soldering tip
72-01-12	4mm dia. chisel soldering tip
72-01-13	12.5mm dia. 45° spade soldering tip
Hot Air Tips	
72-01-51	5.6 O.D./3.6 I.D. (mm) hot air tip
72-01-52	8.6 O.D./6.6 I.D. (mm) hot air tip (std. all models)
72-01-53	11.5 O.D./9.7 I.D. (mm) hot air tip
Adapter	
72-01-14	Adapter (5mm dia. x 8mm pitch) tip
Accessories	
72-01-54	1 1/25.4mm dia., .1 1/25.4mm wide heat shrink attachment
72-01-55	1.25 1/32mm dia., 1.25 1/32mm wide heat shrink attachment (std. UT-200, UT-200Si)
72-02	Protective cap (std. UT-200, UT-200Si)
72-52U	Carrying strap
80-35	Ejector spanner wrench (std. UT-200Si)
80-40	Open end wrench (std. UT-200, UT-200Si)

Ultratip Soldering Tips

- Oxygen-free, copper based Ultratip soldering tips have thick iron and chrome plating for long life and high thermal conductivity
- Ultratips are manufactured using a patented process which produces a uniform iron and chrome plating thickness
- Ultratip soldering tips feature leading-edge combustion chamber/exhaust port design
- All tips are pre-tinned with lead-free solder
- Optional accessories interchangeable between UT-200 and UT-200Si models

NOTE: Users should independently evaluate the suitability of the product for their application.