

DOT-APPROVED RECOVERY CYLINDERS

Features:

- Powder coated cylinder for high gloss, durable finish
- Pre-charged cylinder provides a clean, dry interior
- 3/4" NPT opening accepts 80% fill float switch shut-off device
- Reusable and conforms to DOT-4BA400 specs and ARI guidelines
- Collar design for ease of handling
- Storage and transport of recovered refrigerant gases
- Y-valve for liquid/vapor
- AUS Approved and TC Canadian Approved

30 LB. DOT-APPROVED RECOVERY CYLINDERS



62010 67010 67011

- Size (w x h): 9.125" x 17.52"
- Standard spec.: DOT - 4BA400
- Service pressure: 400 PSI / 2.7 MPa
- Tare weight: 17.99 LB
- Body material: HP295
- Relief valve pressure: 600 PSI / 4.1 MPa
- Nominal water capacity: >26.2 LB / 11.9 L
- Tank test pressure: 800 PSI / 5.5 MPa
- Air tightness test pressure: 400 PSI / 2.7 MPa

Model	62010 without float switch	62011 with float switch	62012 with float switch & NCG Port	64010 without float switch	67010 with float switch	67011 with float switch
Connection	1/4" FL-M (7/16-20)			1/2" ACME		
Color	yellow/gray			blue		yellow/blue

50 LB. DOT-APPROVED RECOVERY CYLINDERS



63010 66010 63010-AUS

- Size (w x h): 12.25" x 18.78"
- Standard spec.: DOT - 4BA400
- Service pressure: 400 PSI / 2.7 MPa
- Tare weight: 28.71 LB
- Body material: HP325 or HP345
- Relief valve pressure: 600 PSI / 4.1 MPa
- Nominal water capacity: >47.7 LB / 21.6 L
- Tank test pressure: 800 PSI / 5.5 MPa
- Air tightness test pressure: 400 PSI / 2.7 MPa

Model	63010 without float switch	65010 with float switch	66010 without float switch	66011 with float switch	66012 with float switch & NCG Port	63010-AUS without float switch (Australian standard)
Connection	1/4" FL-M (7/16-20)			1/2" ACME		1/2" ACME
Color	yellow/gray			yellow/gray		white

100 LB. DOT-APPROVED RECOVERY CYLINDERS



68010

- Size (w x h): 11.25" x 31.81"
- Standard spec.: DOT - 4BW400
- Service pressure: 400 PSI / 2.7 MPa
- Tare weight: 50.5 LB
- Body material: HP325
- Relief valve pressure: 600 PSI / 4.1 MPa
- Nominal water capacity: >92.5 LB / 41.9 L
- Tank test pressure: 800 PSI / 5.5 MPa
- Air tightness test pressure: >87 PSI / 0.6 MPa

Model	68010 without float switch
Connection	1/4" FL-M (7/16-20)
Color	yellow/gray

ENVIRO TANK (REFILLABLE CYLINDER)

30 LB. REFILLABLE CYLINDER



62020-W

- Size (w x h): 8.39" x 20"
- Standard spec.: DOT - 4BA400
- Service pressure: 400 PSI / 2.7 MPa
- Tare weight: 19.9 LB
- Body material: HP295
- Relief valve pressure: 600 PSI / 4.1 MPa
- Nominal water capacity: >30 LB / 13.6 L
- Tank test pressure: 800 PSI / 5.5 MPa
- Air tightness test pressure: >87 PSI / 0.6 MPa

Model	62020-W
Connection	1/4" FL-M (7/16-20)
Color	white

