

87910



ALIGNMENT TOOL BOARD

This board set gives technicians the tools needed to complete today's modern alignments quickly and efficiently. Contains our most popular tools, with a handy plastic peg storage board to keep all your alignment tools in one easy to reference location.

BOARD INCLUDES ONE EACH OF THE FOLLOWING:

Tool Number	Page	Description
8370	163	Tie Rod Puller
37985	164	4-Way Ball Joint/Tie Rod Separator
40840	165	Tie Rod Adjusting Wrench Set (4) 10.5-12mm rods, 12-14mm rods 14-16mm rods, 16-19 mm rods
45938	167	Colorado/Canyon 4WD Alignment Socket
45940	167	GM Express Van Tool
74910	170	Cam Knock Out Punch
77350	171	Heavy Duty Tie Rod Tools
77880	171	Ford OE Sleeve Puller
81139	172	Magnetic Adj. Camber Gauge
83775	172	Cas/Cam Tool - 93 & Up F-Body
85127	173	3/8" Carbide Rotary File
85137	173	3/8" Rotary File for Aluminum
87560	174	Honda 24mm Toe Tool
99918	175	Wheel Spreader Bar - A must for Mercedes

27



PITMAN ARM SEPARATOR

For use on most cars and some light trucks. The tapered wedge easily removes the pitman arm from the shaft with just a few sharp hammer blows.

DIMENSIONS: 1" opening, 12" overall length.

Slide Hammers/Pullers

498



FRONT HUB AND AXLE PULLER

498 removes front hubs on vehicles with independent front suspensions. Remove screw and use it with 499 axle puller to remove axles in compact cars.

498

APPLICATIONS

Compact cars

SET INCLUDES

- 498-1 Yoke
- 498-2 Center screw
- 498-3 Jam nut

499



FLANGE TYPE AXLE PULLER

Flange Type Axle Puller can be used as a regular wheel puller or hub puller, as well as a flange type puller. The bolt circle range is from 4-1/2" to 5-1/2", which covers all cars and small trucks with flange type axles. The four slots allow this tool to be used on 4, 5, or 6 stud designs.

499

APPLICATIONS

All cars and small trucks with flange type axles

SET INCLUDES

- 499-1 Yoke
- 499-2 Center rod assembly
- 499-3 Jam nut
- 499-4 Hammer

Check out our CV Joint Fork #38620 for use with the 499 (page 164)

HONDA ADAPTERS

75980

Honda Adapter #75980 is used in conjunction with the 72509 Ball Joint Press (page 169) and are used with the 67465 Honda Civic Camber Kit on page 94. You need these adapters to push the old bushing out of the stock arm and also to install the new bushing included in the 67465 Kit.



MERCEDES PRESS SETS

75990 76000

These Mercedes Rear Bushing Press Adapter Sets are designed for quick, easy removal of the OE rear control arm bushings and for the insertion of SPC's new adjustable camber bushings. These tool sets are a must for any shop servicing Mercedes vehicles.

75990 - For **28840** (page 83) includes adjusting wrench

76000 - For **28850, 28855 and 28860** (page 83)



TORQUE LIMITING IMPACT EXT. SET

76750

This convenient 8 piece Torque Limiting Extension And Protective Impact Socket Combo Set will have your wheel torque needs covered. It includes the most common wheel mounting socket and torque limits in one great tool kit. The lug nut sockets include protective sleeves and inserts to prevent wheel damage, and are color coded for quick reference. The 1/2" drive set consists of 4 Torque Limiting Extensions: 90, 100, 110 and 120ft/lbs AND 4 Protective Lug Nut Impact Sockets: 17mm, 19mm (3/4"), 21mm (13/16"), and 7/8". Packaged in a blow-molded plastic case.



See page 184 for our Wheel Torque Chart part no. 70050

FORD SUPER DUTY TIE ROD SLEEVE ADJUSTER

77350

This tool is specifically designed for use on the Ford Super Duty trucks as well as most other light trucks and vans. The extra long bar gives you maximum leverage to loosen rusted sleeves without injuring your knuckles. This 8 position tool allows 360° rotation without removing the adjuster block from the sleeve.



APPLICATIONS

Dodge: 2500 & 3500
Ford: Twin I-Beam w/upper and lower ball joints

CAUTION: Not for use with impact wrenches (air tools).

FORD/DODGE/RAM COMBO SLEEVE PULLER

77880

This sleeve puller will pull both OE and most aftermarket camber/caster sleeves quickly and efficiently, usually without damaging the ears of the sleeve. Heat treated high strength steel. Single-unit design with no loose parts.



77928 BRAKE PEDAL DEPRESSOR

An adjustable steel plate extends the length of the bar to put constant pressure on the brake pedal.

77938 STEERING WHEEL HOLDER

A must for proper alignments. This tool securely holds the steering wheel and covered hooks and base prevent damage to the steering wheel or seat.



77938

This product is not a locking device. Use with caution.



77928

This product is not a locking device. Use with caution.

DEEP, THIN WALL FLIP SOCKETS

79230 79240

These 1/2" square drive impact sockets are deep and thin walled to reach areas conventional sockets can't. Each part number provides two sizes.

79230 - 3/4" and 13/16"

79240 - 19mm and 21mm

