

LINCOLN

®

LINCOLN'S MODEL 3624 USED FLUID TANK

- High-strength polyethylene reinforced tank and bowl means no corrosion, no denting, no swelling
- Evacuates easily with standard shop air
- Large capacity: 26 gallon / 100 liter
- Large tool tray and convenient oil filter drain are built into the top of the tank
- Includes fluid level sight gauge, fixed air regulator and safety relief valve
- Professional look and outstanding shop features together in one assembly
- Compatible with virtually all used fluids (motor oil, transmission fluid, power steering fluid, and engine coolant)



**PRESSURIZED EVACUATION
IN A MOBILE, SHOP-FRIENDLY DESIGN**

Loaded with features, the Model 3624 is a great addition to any shop or maintenance facility

Pressurized

Lincoln's model 3624 unique pressurized tank quickly evacuates fluid in just three minutes.*

Durable

Unlike metal tanks, the reinforced high-strength polyethylene will not dent or scratch. The 3624 will maintain its appearance for years and will not swell under pressure.

Safe

The tank's polyethylene material greatly reduces risk to surrounding vehicles. The pressure relief valve and fixed air regulator ensure a safe work environment.

Convenient

The fluid level sight gauge, large tool tray and oil filter drain help optimized labor time and cleanliness.

* At 72°F

Model 3624 Specifications

Capacity:	26 Gallons / 100 Liter
Fluid Types:	Motor Oils, Transmission Fluids, Hydraulic Oil, Power Steering Fluids, Engine Coolant
Min. Bowl Height:	51.25"
Max. Bowl Height:	78.5"
Weight:	74 lbs. (29.5 kg)



Large Tool Tray



Oil Filter Drain



Fixed Regulator and Pressure Relief Valve



Oversized Wheels

