13500 TOYOTA PUMP PULLEY WRENCH

- · Fixed pin dimension for quick easy installation
- Unique bend to clear engine compartment obstacles
- Head shaped for generous clearance around the bolts
- The right tool for the job saves time and money

Applications: TOYOTA

Camry 2.4L 2AZ engines 2002-2011 Other Models 2002-2011



13700 ALL-IN-ONE FLUID STOPPER SET

This unique tool allows technicians to stop fluid draining from various lines found on vehicles, heavy-duty trucks and equipment. These clamp style stoppers feature 4 different sizes for various applications including brake lines, hydraulic lines and smaller coolant lines.



13800 FORD DIESEL 6.0L TENSIONER WRENCH

Ample leverage, 24" long handle provides easier access to 1/2" square socket tensioners and is double ended to fit more Ford 6.0L models for extended coverage.

Applications: FORD

6.0L Diesel engines 2004-2007

13900 FUEL LINE SOCKETS 6-POINT FOR

CUMMINS ENGINES 22mm & 19mm Easily torque the lines correctly, reducing if not eliminating, the possibility of a fuel leak or damaging the fuel line, fuel rail, or fittings. Fits many other engines in the Cummins line-up.

- 13910 22mm for the ISX engines to apply the factory required torque 80 ft./lbs.
- 13920 19mm for the ISB engines to apply the factory required torque of 30 ft./lbs.
- No torque adaptors needed with complicated calculations





13900 SEPARATE PIECES

13910 22mm FUEL LINE SOCKET 6-POINT FOR CUMMINS ENGINES 13910 22mm for the ISX engines to apply the factory required torque of 80 ft./lbs.




13920 19mm FUEL LINE SOCKET 6-POINT FOR CUMMINS ENGINES 13920 19mm for the ISB engines to apply the factory required torque of 30 ft./lbs.



FORD







14200 PNEUMATIC
U-JOINT C-CLIP REMOVER

See Page 13



























See Page 10









89100 CUMMINS SPECIAL



89150 CUMMINS SPECIAL



95650A CUMMINS ENGINE

