

**LOW VIBRATION AIR SAW**

- > 10,000 strokes per minute
- > Only 6.7" long
- > Lowest vibration in its class

Replacement blades -  
**RS18TPIBLADES (5 pk)**  
**RS24TPIBLADES (5 pk)**  
**RS32TPIBLADES (5 pk)**



**SUNEX HD**

**SX6215**

Strokes Per Minute (SPM)	10,000
Stroke Length (in.)	0.38
Weight (lbs.)	0.97
Length (in.)	6.7
Average Air Consumption (CFM)	3
Air Inlet Thread Size (NPTF)	1/4
Min. Hose Size (I.D.)	3/8
Sound Level (dBA)	84.4

**REVERSIBLE CUT-OFF TOOL**

- > Reversible spark direction at 18,000 max rpm
- > Only 87 dBA
- > Weighs only 3.6 lbs.

(Includes 3" cutting wheel)

Replacement wheels (set of 5) - 87602



**SUNEX HD**

**SX6210**

Wheel Size (in.)	3
Free Speed (RPM)	18,000
Weight (lbs.)	2
Length (in.)	8.3
Average Air Consumption (CFM)	3.6
Air Inlet Thread Size (NPTF)	1/4
Min. Hose Size (I.D.)	3/8
Sound Level (dBA)	87

**3" UTILITY CUT-OFF TOOL**

- > Lightweight at 1.6 lbs. but with the power to cut all types of materials
- > Rear exhaust directs air away from the work surface
- > Built-in regulator

(Includes 3" cutting wheel)

Replacement wheels (set of 5) - 87602



**SX233A**

Free Speed (RPM)	20,000
Wheel Size (in.)	3
Weight (lbs.)	1.6
Length (in.)	7.38
Average Air Consumption (CFM)	5
Air Inlet Thread Size (NPTF)	1/4
Min. Hose Size (I.D.)	3/8
Sound Level (dBA)	93

**METAL SHEAR**

- > Hardened shear head can cut up to 18 gauge steel
- > Planetary gearing for long life and heavy duty use
- > Bottom handle diffused exhaust for quiet operation and keeping air away from work surface

Left replacement blade - **RS227B17**  
 Right replacement blade - **RS227B20**  
 Center replacement blade - **RS227B19**



**SX227B**

Strokes Per Minute (SPM)	2,500
Weight (lbs.)	3
Length (in.)	8.5
Average Air Consumption (CFM)	4
Air Inlet Thread Size (in.)	1/4
Min. Hose Size (I.D.)	3/8
Sound Level (dBA)	82