

#### M18 FUEL

#### 3/8" Impact Wrench w/ Friction Ring w/ ONE-KEY<sup>™</sup> Kit 0750 00 0750 00CT (0750 00 Tool Only)

2758-22, 2758-2201 (27	58-20 Iool-Only)
Specifications:	
Fastening Torque	210 ft-lbs
Nut-Busting Torque	210 ft-lbs
IPM	0 - 3,200
RPM	0 - 2,500
DRIVE CONTROL™	4-Mode (Customizable)
Anvil Type	3/8" Friction Ring
Length / Weight	5.9" / 4.2 lbs

Includes: 2758-22 (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC5.0 Battery Packs; 2758-22CT (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> CP2.0 Battery Packs: All Kits Include: Belt Clip, Bit Holder, Multi-Voltage Charger, Carrying Case

#### M18 FUEL

#### 3/8" Compact Impact Wrench w/ Friction Ring Kit

2754-22, 2754-22CT (2754-20 Tool-Only)

#### Specifications:

Fastening Torque	210 ft-lbs
Nut-Busting Torque	210 ft-lbs
IPM	0 - 3,200
RPM	0 – 2,500
DRIVE CONTROL™	4-Mode
Anvil Type	3/8" Friction Ring
Length / Weight	5.9" / 4.2 lbs

Includes: 2754-22 (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC5.0 Battery Packs; 2754-22CT (2) M18™ REDLITHIUM™ CP2.0 Battery Packs; All Kits Include: Belt Clip, Bit Holder, Multi-Voltage Charger, Carrying Case

#### M18<sup>™</sup> 3/8<sup>¶</sup> Compact Impact Wrench Kit

2658-22, 2658-22CT (2658-20 Tool-Only) **Specifications:** 

-	
Fastening Torque	167 ft-lbs
Nut-Busting Torque	167 ft-lbs
IPM	0 – 3,350
RPM	0 - 2,450
Anvil Type	3/8" Friction Ring
Length / Weight	6.0" / 4.1 lbs

Includes: 2658-22 (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC3.0 Battery Packs; 2658-22CT (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> CP1.5 Battery Packs; All Kits Include: Belt Clip, Multi-Voltage Charger, Carrying Case

### M18 FUEL 1/2" Mid-Torque Impact

#### Wrench w/ Pin Detent Kit 2860-22 (2860-20 Tool-Only) Specifications:

Nut-Busting Torque 600 ft-lbs   IPM 0 - 3,000   RPM 0 - 2,400   Anvil Type 1/2" Pin Detent   Length / Weight 6.7" / 5.3 lbs	Fastening Torque	450 ft-lbs
RPM 0 - 2,400   Anvil Type 1/2" Pin Detent	Nut-Busting Torque	600 ft-lbs
Anvil Type 1/2" Pin Detent	IPM	0-3,000
	RPM	0 - 2,400
Length / Weight 6.7" / 5.3 lbs	Anvil Type	1/2" Pin Detent
	Length / Weight	6.7" / 5.3 lbs

Includes: (2) M18™ REDLITHIUM™ XC5.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case

## M18FUEL

#### 1/2" Mid-Torque Impact Wrench w/ Friction Ring Kit

Includes: (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC5.0 Battery Packs, Belt Clip,

2861-22 (2861-20 Tool-Only) Specifications:		
Fastening Torque	450 ft-lbs	
Nut-Busting Torque	600 ft-lbs	
IPM	0 – 3,000	
RPM	0 - 2,400	
Anvil Type	1/2" Friction Ring	
Length / Weight	6.7" / 5.3 lbs	

Multi-Voltage Charger, Carrying Case

3/8" Mid-Torque Impact

2852-22, 2852-22CT (2852-20 Tool-Only)

Wrench w/ Friction Ring Kit

450 ft-lbs

600 ft-lbs

0-3,200

M18 FLEL

Specifications:

Fastening Torque

IPM

RPM

Anvil Type

Nut-Busting Torque

# M18FUEL

**3/4" High Torque Impact** Wrench w/ Friction Ring w/ ONE-KEY<sup>™</sup> Kit 2864-22 (2864-20 Tool-Only)

#### **Specifications:**

Fastening Torque	1,200 ft-lbs
Nut-Busting Torque	1,600 ft-lbs
IPM	0 – 1,850
RPM	0 – 1,850
DRIVE CONTROL <sup>™</sup>	4 Modes (Customizable)
Length / Weight	8.6" / 7.9 lbs

Includes: (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC5.0 Battery Packs, Belt Clip, Multi-Voltage Charger, Carrying Case

#### M18<sup>™</sup> 3/4<sup>¶</sup> High Torque Impact Wrench w/ Friction Ring Kit 2664-22 (2664-20 Tool-Only)

#### **Specifications:**

Fastening Torque	525 ft-lbs
Breakaway Torque	700 ft-lbs
IPM	0 - 2,200
RPM	0 – 1,900
Anvil Type	3/4" Friction Ring
Length / Weight	9.0" / 6.8 lbs

Includes: (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC3.0 Battery Packs, Multi-Voltage Charger, Carrying Case

#### Includes: 2852-22 (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC5.0 Battery Packs; **2852-22CT** (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> CP2.0 Battery Packs; All Kits Include: Belt Clip, Multi-Voltage Charger, Carrying Case



2867-22 (2867-20 Tool-	ue Impact NE-KEY™ Kit <sup>Only)</sup>	
Specifications:		
Fastening Torque	1,500 ft-lbs	
Nut-Busting Torque	1,800 ft-lbs	Contra-
IPM	0 – 2,450	
RPM	0 – 1,650	
DRIVE CONTROL™	4 Modes (Customizable)	REDLITHIU HIGH OUTPUT
Length / Weight	10.9" / 12.9 lbs	

Includes: (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> HIGH OUTPUT<sup>™</sup> XC8.0 Battery Packs, (1) Tool-Free Adjustable Handle, (1) Lanyard Loop, Rapid Charger, Contractor Bag



#### Encolficationa

specifications:		
Fastening Torque	750 ft-lbs	
Nut-Busting Torque	1,100 ft-lbs	
IPM	0 - 2,400	
RPM	0 - 1,800	
DRIVE CONTROL <sup>™</sup>	4-Modes (Customizable)	
Anvil Type	1/2" Friction Ring	
Length / Weight	10.1" / 5.8 lbs	

Includes: (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC5.0 Battery Packs. Multi-Voltage Charger, Contractor Bag

#### MISFUEL 1/2" High Torque Impact Wrench w/ Pin Detent w/ ONE-KEY<sup>™</sup> Kit

2862-22 (2862-20 Tool-Only) **Specifications:** 

#### 750 ft-lbs Fastening Torque Nut-Busting Torque 1,100 ft-lbs 0-2,400 IPM RPM 0 - 1.800 DRIVE CONTROL™ 4-Modes (Customizable) 1/2" Pin Detent Anvil Type Length / Weight 8.1" / 7.2 lbs

Includes: (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC5.0 Battery Packs, Multi-Voltage Charger, Carrying Case







M18	-UEI			
1/2"	High	Torque	Impact	

Wrench w/ Pin Detent Kit

2766-22 (2766-20 Tool-Only) Specifications:

specifications.	1
Fastening Torque	750 ft-lbs
Nut-Busting Torque	1,100 ft-lbs
IPM	0 - 2,400
RPM	0 - 1,850
DRIVE CONTROL™	4-Modes w/ Bolt Removal Mode
Anvil Type	1/2" Pin Detent
Length / Weight	8.1" / 7.1 lbs

Includes: (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC5.0 Battery Packs, Multi-Voltage Charger, Carrying Case

# M18<sup>™</sup> 1/2" High Torque Impact Wrench w/ Pin Detent Kit

2662-22 (2662-20 Tool-Only)

Specifications:

Fastening Torque	450 ft-lbs
Breakaway Torque	640 ft-lbs
IPM	0 - 2,200
RPM	0 – 1,900
Anvil Type	1/2" Pin Detent
Length / Weight	8.9" / 6.7 lbs



Includes: (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC3.0 Battery Packs, Multi-Voltage Charger, Carrying Case



#### M18 FUEL **1/2" High Torque Impact Wrench** w/ Friction Ring w/ ONE-KEY™ Kit 2863-22 (2863-20 Tool-Only)

Specifications:

Fastening Torque	1,000 ft-lbs
Nut-Busting Torque	1,400 ft-lbs
IPM	0 – 2,100
RPM	0 – 1,750
DRIVE CONTROL™	4-Modes (Customizable)
Anvil Type	1/2" Friction Ring
Length / Weight	8.4" / 7.6 lbs



Includes: (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC5.0 Battery Packs, Multi-Voltage Charger, Carrying Case

#### M18 FUEL 1/2" High Torque Impact Wrench w/ Friction Ring Kit 2767-22 (2767-20 Tool-Only)





Specifications:	
Fastening Torque	1,000 ft-lbs
Nut-Busting Torque	1,400 ft-lbs
IPM	0 – 2,100
RPM	0 – 1,750
DRIVE CONTROL™	4-Modes w/ Bolt Removal Mode
Anvil Type	1/2" Friction Ring
Length / Weight	8.4" / 7.5 lbs

Includes: (2) M18<sup>™</sup> REDLITHIUM<sup>™</sup> XC5.0 Battery Packs, Multi-Voltage Charger, Carrying Case



