

Blasters, Accessories & Abrasives

ALC PROFESSIONAL PRESSURE BLASTERS

Deadman Blasters Manual pull up tank closure / Adjustable abrasive flow valve / 80 - 125 psi Operating pressure / Minimum air volume of 7 CFM @ 80 psi / Pressure gauge / Pressure relief valve - 125 psi / Pressure relieving ball valve



• 44 lbs. / Ships UPS



40001 (F-65DM)

• 55 lbs. / Ships UPS



• 53 lbs. / Ships UPS



40003 (F-110DM)

• 63 lbs. / Ships UPS



• 76 lbs. / Ships UPS



40005 (F-300DM)

• 133 lbs.

Model No.	Blast Hood	Blast Time	Blast Hose Size	Ceramic Nozzle Size	Moisture Separator	Frame	Tank Dimensions	Overall Height	Wheel Size	Tank Volume	Approximate Capacity
40000	Standard	15-20 Min.	1/2" ID x 8'	1 ea 1/8" / 1 ea 3/32"	Optional	Tubular Steel	10" x 14"	35"	6"	0.45 cu. ft.	45 lbs.
40001	Bump Hat	20-30 Min.	1/2" ID x 10'	2 ea 1/8" / 1 ea 3/32"	Optional	Welded Steel	12" x 17"	29.5"	6"	0.65 cu. ft.	65 lbs.
40002	Standard	30-45 Min.	1/2" ID x 8'	1 ea 1/8" / 1 ea 3/32"	Optional	Welded Steel	10" x 25"	34"	6"	0.9 cu. ft.	90 lbs.
40003	Bump Hat	35-50 Min.	1/2" ID x 10'	2 ea 1/8" / 1 ea 3/32"	Optional	Welded Steel	12" x 22"	32"	8"	1.1 cu. ft.	110 lbs.
40004	Bump Hat	45-60 Min.	1/2" ID x 15'	2 ea 1/8" / 1 ea 5/32"	Included	Welded Steel	12" x 27"	37"	8"	1.5 cu. ft.	150 lbs.
40005	Bump Hat	1-2 Hours	1/2" ID x 25'	2 ea 1/8" / 3 ea 5/32"	Included	Welded Steel	16" x 28"	40"	10"	2.5 cu. ft.	250 lbs.

Remote Blasters Automatic tank closure / Adjustable abrasive flow valve / 80 - 125 psi Operating pressure / Minimum air volume of 40 CFM @ 80 psi / Pressure gauge / Pressure relief valve - 125 psi



40011 (F-600R)

- · Heavy-duty blast hood
- 1" ID x 25' Blast hose
- 2-3 Hour blast time from 24" x 39" (6 cu. ft.) tank (600 lbs. capacity)
- Pressure choke valve
- Manual pressure release
- Dual remote media valves
- Welded steel frame
- (1) 1/4" Tungsten carbide nozzle included
- Moisture separator included
- Overall height: 52" with 16" wheels
- 425 Lbs. (skidded)



Converts Your Pressure Blaster Into a Soda Blaster in Minutes!

Conversion Kit



- Removes paint and graffiti without harming the surface
- Cleans engine compartments & other areas without harming the surface
- 2 Year warranty
- Environmentally friendly

40416 with 1/2" & 3/8" fittings

Complete Kits

Includes Pressure Blaster Kit and the Soda Blaster Attachment

40002SB 100 Lb.

40003SB 110 Lb. ASME Certified



For Full Line Product Information and Additional Information

©2013 S&H Industries, 5200 Richmond Road, Cleveland, Ohio 44146