



Pole assembly shall be constructed of 6" square, 3/16" wall structural steel tube suitable for a 39" in-ground installation. Pole shall be shipped in 2 pieces and attached in the middle by means of two 3/8" x 3" x 12" steel bar, and eight 1/2" x 3/4" button head cap screws forming a single, straight, rigid pole. Connecting points shall be covered by pole padding if padding is included in the system. 45° extension arm shall be 6" square, 3/16" wall structural tube with a 4" square, 1/8" wall steel tube horizontal support and 1/4" thick steel backboard support plate. Pole shall be designed so that rim mounts directly to pole to minimize stress on the backboard. Extension arm shall be mounted by means of 6 each 5/8" grade 8 bolts. Pole system shall provide a minimum setback from the front of pole to front of backboard of 60". System can be ordered with an optional 72" setback (BA870AXL) if desired. Entire pole system shall have a textured black polyester powder coated finish and carry a lifetime functional warranty. Vertical pole shall be capped to keep out rain. Backboard shall be 42" x 72" official size 1/2" clear unbreakable polycarbonate with a limited lifetime warranty. Polycarbonate shall be framed with aluminum extensions and have a white border and shooters square. Rim shall be the flexible type with official-sized 5/8" diameter ring and one-piece net attachments. Rim shall have orange powder coated finish and a 1-year limited warranty. Installation to be completed in accordance to manufacturers instructions. Do not scale drawings. Entire weight shall be 480#.



PRODUCT SPECIFICATION

BA873U-BK ULTIMATE™ POLYCARBONATE PLAYGROUND BASKETBALL SYSTEM

REVISED 5/2/22 L.M.