

Bench legs shall be constructed of 2" x 2" square tubing with a 12 ga. wall thickness and a polyester powder coated finish. 3" diameter rubber molded feet shall attach to the bottom of legs at 4 places to prevent scratching of floors. All exposed tube ends shall be enclosed by means of molded plastic end caps. Bench shall be 7 1/2' in length to accommodate up to 5 players. Seat and seat back shall be extruded aluminum with clear anodized finish designed to provide a 10" wide plank with an overall thickness of 1 3/4" and have molded end caps. The aluminum planks shall have a minimum cross section thickness of 2/25". For Powder Coated Aluminum Seat Planks order optional BL07SEAT1-XX for each plank. Choose any combination of colors: Royal, Scarlet, Navy, Forest Green, Black and White. Plank and setback shall be attached to two tubular leg assemblies. All assembly hardware shall be zinc plated. Bench shall carry a 5-year limited warranty on legs and a 2-year limited warranty on aluminum planks and shall weigh 45# on BNP0701BAA. Installation to be completed in accordance to manufacturer's instructions. Do not scale drawings.



REVISED 3/6/18

603 L Street, Lincoln, NE 68508 - Phone: (800) 247-7668 - Fax: (800) 638-0698 - www.bisoninc.com - info@bisoninc.com