



2400 Boston Street, Suite 200, Baltimore, Maryland 21224  
Phone: 410-675-2100 or 800-543-3840

Revised: 1/25/2016

## DAP<sup>®</sup> KWIK SEAL<sup>®</sup> Adhesive Caulk – White & Almond

- Cured caulk is mold & mildew resistant
- Bonds like a glue, seals like a caulk
- 100% waterproof
- Paintable
- Easy water clean-up & low odor
- Interior

**Packaging:** 5.5 fluid ounces (162 mL) and 10.1 fluid ounces (300 mL)  
**Color:** White, Almond  
**UPC Numbers:** 70798 18001, 70798 18013, 70798 18002, 70798 07049, 79798 07050

### Company Identification:

Manufacturer: DAP Products Inc., 2400 Boston St., Baltimore, Maryland 21224  
Usage Information: Call 1-888-DAP-TIPS or visit [dap.com](http://dap.com) & click on “Ask the Expert”  
Order Information: 800-327-3339  
Fax Number: 410-558-1068  
Also, visit the DAP website at [www.dap.com](http://www.dap.com)

### Product Description:

DAP<sup>®</sup> KWIK SEAL<sup>®</sup> KITCHEN & BATH ADHESIVE CAULK is an easy-to-use adhesive caulk that bonds like a glue and seals like a caulk. It provides a 100% waterproof seal around tubs, sinks, showers, countertops and fixtures. It can also be used to repair loose tiles and fixtures. KWIK SEAL<sup>®</sup> tools easily and is tack free in 15 minutes. It is paintable, low in odor and cleans up easily with water. Interior use.

### Suggested Uses:

#### *Ideal for caulking & sealing:*

- *Tubs*
- *Sinks*
- *Backsplashes*
- *Showers*
- *Countertops*
- *Toilets*
- *Fixtures*
- *Loose Tile Repair*
- *Cracks and Joints*

***Adheres To:***

- *Ceramic/Porcelain*
- *Glass*
- *Most Plastics*
- *Granite, Cultured Marble & Natural Stone*
- *Wood*
- *Metal*
- *Drywall*
- *Fiberglass*
- *Painted Surfaces*

### **Performance Characteristics:**

- Cured caulk is mold & mildew resistant
- 100% waterproof
- Easy water clean up
- Low odor
- Paintable

### **Surface Preparation & Application:**

1. Surface must be clean, dry and free of all old sealant, dirt, dust, debris and grease. Rubbing alcohol is recommended for removing soap film and soil.
2. Remove cap (from tube). Cut nozzle at a 45° angle to desired bead size.
3. If using the cartridge, load into caulk gun.
4. Fill gap with caulk, pushing caulk ahead of nozzle.
5. For a neat finish, smooth bead of caulk immediately with a finishing tool.
6. Allow caulk to dry for at least 2 hours before (longer in cool/humid conditions) before painting with latex or oil-based paints.
7. Wait 36 hours before exposing to water.
8. Clean up excess uncured caulk with damp sponge before it skins over. Scrape or cut away excess cured caulk. Clean hands and tools with warm, soapy water.
9. Reseal tube/cartridge for future use.

### **For Best Results:**

- Apply in temperatures above 40°F.
- Not for continuous underwater use, high temperature surfaces or surface defects.
- Joint width should not exceed 3/8". If joint depth exceeds 3/8", use foam backer rod.
- Allow caulk to dry for at least 2 hours before (longer in cool/humid conditions) before painting with latex or oil-based paints.
- Wait 36 hours before exposing to water.
- Store product away from extreme heat or cold.

### **Typical Physical & Chemical Characteristics:**

Vehicle:	Latex polymer
Solids:	82 % by weight
Filler:	Calcium carbonate
Density:	13.9 lbs/gal
Specific Gravity:	1.67
Tooling Time:	10 minutes
Tack Free Time:	15 minutes
Paintable:	Yes
Odor:	Very mild
Consistency:	Smooth and creamy
Volatile:	Water
Flash Point:	None
Temperature Service Range:	-20° F to 150°F
Temperature Application Range:	40°F to 100°F
Freeze Thaw Stability:	Passes 5 Cycles
Applications:	Interior

Shelf Life: 12 months  
Coverage: 5.5 fluid ounces: 30 linear feet at a 3/16" diameter bead or two average size bathtubs  
10.1 fluid ounces: 55 linear feet or four average size bathtubs  
SDS No.: 00010009001

**Clean Up & Storage:**

Clean up excess uncured caulk with a damp cloth/sponge before it skins over (approximately 15 minutes). Excess cured caulk must be cut or scraped away. Clean hands and tools with warm, soapy water. Store in a cool, dry place away from extreme heat or cold.

**Safety:**

**Caution!** Contains petroleum distillates. Use in well-ventilated area. Do not get in eye or on skin. Use gloves and safety glasses. **Keep out of reach of children. Do not take internally. Warning:** This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. In an **emergency**, call your poison control center at 1(800) 222-1222. See product label or Safety Data Sheet for additional safety information. You can obtain an SDS sheet by going to [dap.com](http://dap.com) or by calling 1-888-DAP-TIPS.

**Guarantee:**

If product fails to perform when used as directed, within one year of date of purchase, return used container and sales receipt to DAP Products Inc., TCS, 2400 Boston St., Baltimore, MD 21224 for replacement product or sales price refund. DAP is not liable for incidental or consequential damages.