



Products for Your Home

<input type="text"/>	SITE SEARCH	HOME	PRODUCTS	DESIGN WITH LIGHT	COUPONS / SPECIAL OFFERS
----------------------	-----------------------------	----------------------	--------------------------	-----------------------------------	--

[Where to Buy](#) | [FAQs](#) | [Contact Us](#)[Home](#) > [Products](#) > 26422**26422 – LU70/MED/CP**

GE Lucalox® High Pressure Sodium B17

[Print](#)[Features & Photos](#)[Technical Specifications](#)[WHERE TO BUY](#)[View Larger](#)**PRODUCT INFORMATION**

ANSI Code	S62
Base	Medium Screw (E26)
Product Code	26422
Description	LU70/MED/CP
UPC	043168264228

GENERAL CHARACTERISTICS

Lamp type	High Intensity Discharge - High Pressure Sodium
Bulb	B17
Base	Medium Screw (E26)
Bulb Finish	Clear
Wattage	70
Rated Life (MIN)	24000 hrs
Bulb Material	Hard glass
Lamp Enclosure Type (LET)	Open or enclosed fixtures
Additional Info	TCLP compliant
Primary Application	Motion-Sensing & Security

PHOTOMETRIC CHARACTERISTICS

Initial Lumens	6400
Mean Lumens	5450
Nominal Initial Lumens per Watt	91
Color Temperature	1900 K
Color Rendering Index (CRI)	22
Effective Arc Length	1.060000 in (26.924000 mm)

ELECTRICAL CHARACTERISTICS

Burn Position	Universal burning position
Open Circuit Voltage (RMS lag ballast) (MIN)	110 V
Warm Up Time to 90% (MIN)	3 min
Warm Up Time to 90% (MAX)	4 min
Hot Restart Time to 90% (MAX)	0.670 min

DIMENSIONS

Maximum Overall Length (MOL)	5.4300 in (137.9 mm)
Nominal Length	5.430 in (137.9 mm)
Bulb Diameter (DIA)	2.125 in (53.9 mm)
Light Center Length (LCL)	3.430 in (87.1 mm)

 CAUTIONS & WARNINGS

[See list of cautions & warnings](#)

Home | Products | Design with Light | Coupons / Special Offers | Where to Buy | FAQs | Contact Us
 GE Around the World | Site Map | Commercial Products & Solutions | Press Room | Corporate
 Careers | Investor Information | Privacy Policy | Accessibility Statement | Terms of Use

Copyright 2011 General Electric Company

Sign up for our e-Ne

Enter E-Mail Address