

ALKYD

• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®
INDUSTRIAL
— CHOICE —**TECHNICAL DATA****IC-08****S1600 SYSTEM
INVERTED STRIPING PAINT****DESCRIPTION AND USES**

The S1600 System Inverted Aerosol Striping Paint is designed specifically for creating crisp and clean, long-lasting lines. It is ideal for use to mark aisles, lift truck routes, pallet positions, hazardous areas and commercial parking lots.

These products are suitable for interior or exterior use on concrete, grass, gravel or other types of pavement.

The S1600 System complies with USDA FSIS regulatory sanitation performance standards for food establishment facilities.

PRODUCTS

SKU	Description
1627838	Blue
1648838	Yellow
1665838	Red
1691838	White
263446	Dark Blue
1677838	Black

PACKAGING

20 fl. oz. aerosol container (18 ounce fill weight)
6 aerosols per carton

PRODUCT APPLICATION**SURFACE PREPARATION**

ALL SURFACES: Remove loose contaminants by sweeping the surface before application of the coating. Grease, oil and chemical contaminants are best removed by washing the surface with Pure Strength® Cleaner/Degreaser item #3599402, commercial detergent or other suitable cleaner. Rinse thoroughly with fresh water and allow to fully dry.

APPLICATION

Use when temperature is above 32°F (0°C) and humidity is below 85% to ensure proper drying. Protect surrounding surfaces from overspray. Overspray can carry a significant distance.

The Inverted Striping sprays are designed for use with the Rust-Oleum Striping Machine item #2395000. Follow machine directions for proper use. The width of the stripe can be varied from 2 to 4 inches wide by adjusting the position of the can holder on the Striping Machine. For best results be sure the Striping Machine is in motion before squeezing the trigger and release the trigger before stopping.

The inverted striping aerosols can also be used with the #2388000 Striping Wand.

PHYSICAL PROPERTIES

		INVERTED STRIPING PAINT
Resin Type		Modified alkyd
Pigment Type		Varies with color
Solvents		Acetone, Xylene, and Toluene
MIR		Maximum value of 1.2
Fill Weight		18 oz.
Practical Coverage		Approximately 150 linear feet at 4" wide (46 meters at 10 cm.)
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Tack-free	<10 minutes
	Handle	30 minutes
	Recoat	Anytime
Shelf Life		5 years
Safety Information		For additional information, see SDS

Calculated values are shown and may vary slightly from the actual manufactured material.

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

RUST-OLEUM
INDUSTRIAL BRANDSRust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061
An RPM CompanyPhone: 877-385-8155
www.rustoleum.com/industrialForm: GDH-26
Rev.: 071316