		REV.	DESCR	IPTION		DATE
		A B				02-2007
1 2 2 2 4 S-Video / M	(4 3 S-Video	- 2)) - 1
	Pin Assignment S-Video S-Video Male Female				ART NO. DS2-D11DLG	CABLE LENGTH L ft
	l <u>Spir</u> 2 <u>Spir</u> a	L Spiral Gnd Coax L(White)				12 ft
	E E E E E E E E E E E E E E E E E E E					25 ft
					022-01120G	50 ft
					0S2-011756	75 ft
				г	025-077HDC	100 ft
	ITEM NUMBER		7025-077××C		DRAWER	M₽⊅
5 S-Video (MiniDIN4) Hood, Black Molded PVC	TITLE	TITLE S-Video Male to S-Video Fem Video Cable, Gold Plated Connectors		Female	CHECKED	MAC
4 S-Video (MiniDIN4) Male w/Gold Flash Contacts, Gold Plated Connector	_			4	APPROVED	MAC
3 S-Video (MiniDIN4) Hood, Black Molded PVC	MATERIAL	1	SCALE			
2 S-Video (MiniDIN4) Male w/Gold Flash Contacts, Gold Plated Connector	REV.	A	UNIT	INCH	┨ ⊕	
2 x Mini-Coax ElC x 28AWG (O.12mm*7) w/Al-Foil + Braid(41*O.12mm)], 75 Ohm, Black Outer PVC Jacket, OD: 6.4mm	DRAWING NO:					
NO. SPECIFICATIONS	_				888-212-8	
BOM LIST					CableWho	lesale •