

**RAYTHEON**TECHNICAL  
INFORMATION  
SERVICE

# Technical Information

**6GV8  
9GV8**
**TRIODE-PENTODE**

The 6GV8 is a combined triode and beam pentode especially intended for use in vertical output stage, particularly 110° picture tubes. Special attention has been paid to properties important for this application, such as microphonism and linearity.

The 9GV8 is identical to the 6GV8 except for heater characteristics.

**ELECTRICAL DATA****HEATER CHARACTERISTICS:**

	<u>6GV8</u>	<u>9GV8</u>
Heater voltage (ac or dc) . . . . .	$6.3 \pm 10\%$ □	$9.5 \bullet$
Heater current . . . . .	0.90●	$0.600 \pm 6\%$ □ amp
Heater positive with respect to cathode		
DC component . . . . .	100	100 volts
Total DC and peak . . . . .	200	200 volts
Heater negative with respect to cathode		
Total DC and peak . . . . .	200	200 volts
Heater warm-up time . . . . .		11 sec.

**DIRECT INTERELECTRODE CAPACITANCES:**



	<u>With shield</u>	<u>Without shield</u>
Pentode Section		
Grid #1 to plate . . . . .	.50	.45 pf
Input: G1 to (h+k+g2+g3+int. shield). . . . .	12.0	12.0 pf
Output: p to (h+k+g2+g3+int. shield). . . . .	10.0	7.9 pf
Triode Section		
Grid to plate . . . . .	1.6	1.7 pf
Input: g to (h+k) . . . . .	4.3	4.5 pf
Output: p to (h+k+t). . . . .	3.1	2.0 pf

**DESIGN MAXIMUM RATINGS: (See EIA standard RS-239)**

	<u>Triode</u>	<u>Pentode</u>
Plate voltage . . . . .	250	250 volts
Peak plate voltage . . . . .	---	2000 volts
Plate dissipation . . . . .	0.5	7 watts
Grid #2 voltage . . . . .	---	250 volts
Grid #2 dissipation . . . . .	---	2 watts
Grid #1 ckt. resistance (fixed bias) . . . . .	1.0	1 megohm
Grid #1 ckt. resistance (cathode bias) . . . . .	3.3	2.2 megohm
Cathode current . . . . .	15	75 ma

**CHARACTERISTICS AND TYPICAL OPERATION:**

	<u>Triode</u>	<u>Pentode</u>
Plate voltage . . . . .	100	170 volts
Grid #2 voltage . . . . .	---	170 volts
Grid #1 voltage . . . . .	-0.8	-15 volts
Plate current . . . . .	5	41 ma
Grid #2 current . . . . .	---	2.7 ma
Transconductance . . . . .	6500	7500 $\mu$ hos
Amplification factor . . . . .	50	7 ( $g_1$ to $g_2$ )
Plate resistance . . . . .	7600	25,000 ohms

**PHYSICAL DIMENSIONS****BASING****PIN CONNECTIONS**

1. Plate, triode section
2. Grid #1, triode section
3. Cathode, triode section
4. Heater
5. Heater
6. Plate, pentode section
7. Grid #2
8. Grid #3, cathode, pentode section, internal shield
9. Grid #1, pentode section



# 6GV8 9GV8

## TRIODE-PENTODE

### ELECTRICAL DATA (Cont'd.)

#### INSTANTANEOUS PLATE KNEE CHARACTERISTICS: (Pentode section)

Plate voltage . . . . .	50	65 volts
Grid #2 voltage . . . . .	170	210 volts
Plate current . . . . .	200	240 ma
Screen grid current. . . . .	40	50 ma
Negative grid #1 voltage . . . . .	-1	-1 volt

- The equipment designer shall design equipment so that the heater voltage for the 6GV8 and the heater current for the 9GV8 are centered at the specified bogey value with heater supply variations restricted to maintain heater voltage (or current) within the specified tolerance.
  - Heater current at bogey heater voltage.
  - Heater voltage at bogey heater current.