



EntryGuard™ FKFP-AC-PRO2 NEW INSTALLATION OR RETROFIT

Your Face is your Key Access Control Networkable & Addressable



The FKFP-AC-PRO2 works with both versions of FaceKey's Software. Software is sold separately.

Three Factor ID is Available: The design permits the PRO2 to operate in one, two or three factor mode. The PRO2 has five ID methods which affords 19 ID combinations. The ID methods are: face, fingerprint, PIN, password or card reader. The ID methods can be presented in any order.

The FaceKey™ Face & Fingerprint PRO2 unit can function as a standalone device or multiple units can be connected over a network. Each unit is TCP/IP addressable and has a unique MAC address visible on the internet.

The FKFP-AC-PRO2 when used for access control is a full featured access control device; see "Benefits and Features". The FKFP PRO2 unit is available with a RFID card reader (HID, Generic or Mifare). The PRO2 when used as a time clock has the same features except the unit does not unlock doors.

Software: FaceKey's Software automatically synchronizes all FaceKey PRO2 devices with the network and manages the face and fingerprint templates. If the network fails, the units will continue to operate and collect data which will be uploaded when communication with the network is reestablished.

Scalable: The FaceKey Software database supports an unlimited number of devices and users. Each PRO2 unit can accommodate up to 4000 fingerprint templates and 1500 faces in 1:many mode. In 1:1 mode, the PRO2 can accommodate 4000 fingerprints templates and 4000 face templates. Call FaceKey for units with additional templates.

Standard FKFP-PRO2 model and part nos. Contact FaceKey for special order products. (Optional WIFI Available)

Description	Model #	Part #
Standard	FKFP-PRO2	8033152
Generic Card	FKFP-PRO2+EM	8033153
Mifare Card	FKFP-PRO2+MIL	8033155
HID/Desfire Card	FKFP-PRO2+HID	8033158

FaceKey™ Corporation

900 NE Loop 410, Suite D401
San Antonio, TX 78209
210-826-8811

www.facekey.com

Email: info@facekey.com

Benefits and Features:

- Easy installation.
- Connects directly to local area network.
- Red and green status indicators.
- 2.8" TFT display.
- Optical fingerprint reader with cover.
- Auto correction contrast & brightness.
- Face recognition.
- Fingerprint recognition.
- Keypad (Lighted).
- Doorbell.
- Three factor ID: (19 ID combinations)
 - Face+fingerprint+card (example).
- Professional access control features
 - 50 Time zones.
 - 10 Unlock combinations.
 - 5 Groups.
 - Anti-pass back.
 - Tamper switch.
 - Alarm output.
 - Door sensor input.
 - Exit request input.
 - Doorbell button.
- Holiday schedule.
- Acknowledgment of acceptance: LED indicator, display indication and voice reply.
- Auxiliary input.

Technical Specifications:

- Identification (Fingerprint)
 - Time: <=0.8s
 - FAR: <=0.0001%
 - FRR: <=1%
- Identification (Face)
 - Time <=3s
- Transaction Capacity:
 - Event Log 100,000 events
 - Faces "see Scalable"
 - Fingerprints "see Scalable"
- Connectivity: TCP/IP, RS485 Wiegand output/input (26 or 34 bit standard)
- Dimensions: 7.4 (L) X 3.3 (W) X 2.5 (D) in.
- Voltage input: 12 VDC (power supply not included)
- Indoor use only
- Temperature range: 32°- 113°F (0°-45°C)