

# FS-15CL



FS-15CL CLEAR MOLDED CYLINDER LEXAN® FACE SHIELD SUPER HARD COAT **Ref.** WELFS15CL\_



## Product specifications

FS-15CL features Lexan®, a superior quality optical grade material that's highly impact resistant and heat tolerant with limited scratch resistance.

Offers splash and impact protection.

Universal Hole Pattern on Elvex® face shields, also fit on the more popular headgear brands. Elvex® face shields fit to our HG-25 and HG-35 headgears.

Material: Molded Cylinder Lexan®

### **COLOR**

Clear

### SIZE

No size



#### Product Use - Risks



Shock



Heat



UV / TR



Agriculture / Green areas



Construction / Civil engineering



Second work



Heavy industry



Light industry



Services / Logistics



Hygiene environment



Oil / Gas



Mining



Wind/Energy

Product's highlights & user's benefits					
Industry Leading Thickness: 0.078 inches					
Die cut universal hole pattern fits most competitive headgear options.					
Heat Tolerance: up to 265 degrees					
Dimensions: 8 in. x 15.5 in. x .078 in.					
UV Protection: 99.9% between 180-380nm					



# Certifications and Standards

#### **USA STANDARDS**



ANSI Z87.1-2010(+) American National Standards Institute - Occupational and didactic Personal Eye and Face Protection Devices.

.: High Velocity Impact .: High Mass Impact

References					
References	Bar code	COLOR	SIZE	•	À
WELFS15CL	7292946122860	Clear	No size	50	-