

Lightweight Beam Trolley Anchor

The FallTech™ Beam Trolley is a lightweight mobile anchorage connector solution for use in Personal Fall Arrest Systems. Positioned anywhere along an overhead horizontal I-beam, the Beam Trolley will effortlessly follow the user and is ideally suited for use with SRLs in general industry applications.



7712 | Beam Trolley Anchor

Material Specifications

D-ring:	Aluminum Alloy; 5,000 lbs Min Static Strength
Crossbar:	Aluminum Alloy

Performance Specifications

Static Strength:	5,000 lbs
Min Use Temperature:	10° Fahrenheit
ANSI Anchor Class:	Type D
ANSI User Capacity:	310 lbs or less
OSHA User Capacity:	425 lbs or less

- Fits I-beams from 4" to 18" wide and up to 1¾" thick.
- Features aluminum crossbar, side plates and 360° swiveling D-ring.
- High density Nylacast wheels provide high continuous service temperature resistance and low moisture absorption rate.
- Stainless Steel wheel guards and fasteners plus sealed stainless steel wheel bearings.
- Features simple beam width adjustment with secondary locking detent pin.
- Weighs only 8½ lbs.

Relevant Standards

ANSI	Z359.18-2017
OSHA	1926.502

Product descriptions and specifications herein may change without notice.