

# Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014



Alexander Andrew, Inc. 1306 S. Alameda St Compton, CA 90221

Declaration #

B0317095a

Declaration Date

3.28.17

Tested Item # **7080BFDM** **ComforTech ACT Climbing Non-belted Full Body Harness**

Additional Items Conforming Under this Declaration:

7080BFDS 7080BFDL 7080BFDXL

Alexander Andrew, Inc. declares that the product(s) listed above is in conformity with the requirements of the following performance standard(s):

**OSHA 1910.66**

Conformity Assessment Method in accordance with ANSI/ISEA 125-2014

Level 1

Level 2

Level 3

**Level 1:** FallTech Lab  
Outside the Scope of  
ISO/IEC Standard 17025:2005

**Level 2:** FallTech Lab  
Within the Scope of  
ISO/IEC Standard 17025:2005

**Level 3:** Independent 3rd Party Lab  
accredited to  
ISO/IEC Standard 17025:2005

Supporting  
Documentation

PC-1082

Authorized Signature

Name Dustin Hawkins

Title VP Business Development

Date 4.3.17

## FallTech Test Report

<b>Test Report No.</b>	PC-1082	<b>Rpt. Date</b>	3/28/2017	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	OSHA 1910 Subpart I App. D: (d) (3) (ii)				
<b>Part No.</b>	7080BFDM	<b>Part No. Revision</b>	A				
<b>Part Description</b>	Full Body Harness						
<b>Test Request No.</b>	PC-1082	<b>Date Complete</b>	3/27/2017				
<b>Test Operator(s)</b>	Yesbet Sierra, Jay Sponholz						

### Material/Sample Identification

Sample ID	Description
D1	Full Body Harness
S1	Full Body Harness

### Test Summary

Test Specification	Test Criteria	Test Result	Pass/Fail	
OSHA 1910 Subpart I App. D: (d) (3) (ii)	Dynamic Performance Dorsal D-ring (Feet First) 72" Drop height	Maximum Arrest Force ≤ 2520 Lbf	1039.1 Lbf	Pass
	Dynamic Performance Dorsal D-ring (Feet First) 72" Drop height	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Feet First) 72" Drop height	Remain Suspended for ≥ 1 Minutes	1 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Feet First) 72" Drop height	Angle at Rest = No Angle requirement	1.3°	N/A
	Dynamic Performance Dorsal D-ring (Feet First) 72" Drop height	Harness Stretch = Shall Be Measured	34.8"	Information



## FallTech Test Report

<b>Test Report No.</b>	PC-1082	<b>Rpt. Date</b>	3/28/2017	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	OSHA 1910 Subpart I App. D: (d) (3) (ii)				
<b>Part No.</b>	7080BFDM	<b>Part No. Revision</b>	A				
<b>Part Description</b>	Full Body Harness						
<b>Test Request No.</b>	PC-1082	<b>Date Complete</b>	3/27/2017				


### Test Summary

Test Specification	Test Criteria		Test Result	Pass/Fail
OSHA 1910 Subpart I App. D: (d) (3) (ii)	Dynamic Performance Sternal D-ring (Feet First) 24" Drop height	Maximum Arrest Force ≤ 2520 Lbf	2024.8 Lbf	Pass
	Dynamic Performance Sternal D-ring (Feet First) 24" Drop height	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Sternal D-ring (Feet First) 24" Drop height	Remain Suspended for ≥ 1 Minutes	1 Minutes	Pass
	Dynamic Performance Sternal D-ring (Feet First) 24" Drop height	Angle at Rest = No Angle requirement	28.0°	N/A
	Dynamic Performance Sternal D-ring (Feet First) 24" Drop height	Harness Stretch = Shall Be Measured	8.4"	Information

### Conclusion

FallTech P/N 7080BFDM Rev. A meets the requirements of OSHA 1910 Subpart I App. D (d) (3) (ii)

### Report Signatories and Approval

Lab Quality Manager		Date	3/28/2017
Witnessed by	Not Required	Date	N/A

