Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014 and ANSI/ASSP Z359.7-2019



Alexander Andrew, Inc. 1306 S. Alameda St Compton, CA 90221 (800) 719-4619

Declaration #	B0720139b	Declaration Date	7/24/2020

Tested Item # 8143SM FT-Iron FBH 1D Standard Non-belted, TB Legs/QC Chest

Additional Items Conforming Under this Declaration:

8143XS 8143BXS 8143B2X3X

8143LXL 8143BSM 81432X3X 8143BLXL

Alexander Andrew, Inc. declares that the product(s) listed above is in conformity with the requirements of the following product standard(s):

ANSI Z359.11-2014

Conformity Assessment Method in accordance with ANSI/ISEA 125-2014

Level 1 Level 2 X Level 3

Level 1: FallTech Lab
Outside the Scope of
ISO/IEC Standard 17025:2005

Level 2: FallTech Lab Within the Scope of ISO/IEC Standard 17025:2005 Level 3: Independent 3rd Party Lab accredited to ISO/IEC Standard 17025:2005

Supporting PC-1898 Documentation

Authorized Signature

Name Zachary Winters Title Engineering Manager Date 4/9/2021

ACCREDITED

International Accreditation Service, Inc 3060 Saturn St, Ste 100

Brea, CA 92821 +1 562-364-8201

FallTech Lab - TL-594 ISO/IEC 17025:2017

Alexander Andrew Inc dba FallTech



FallTech Testing Laboratory

FallTech Test Report						
Test Report No.	PC-1898	Rpt. Date	7/24/2020	Rpt. Rev		Rev Date
Report Prepared For	FallTech	allTech				
Initiated By	Dan Redden	Toot Chapification(a)		ANSI Z359.11-2014 4.3.5, 4.3.3, 4.3.4, 4.3.7		7
Part No.	8143SM			Part No. Re	vision	А
Part Description	Ironworker Full Body Harr	ronworker Full Body Harness				
Test Request No.	PC-1898		Date Comp	lete	7/23/2020	
Test Operator(s)	Jay Sponholz					

	Material/Sample Identification				
Sample ID	Description				
SST1	Full Body Harness				
SST2	Full Body Harness				
SST3	Full Body Harness				
DPTFF1	Full Body Harness				
DPTFF2	Full Body Harness				
DPTFF3	Full Body Harness				
DPTHF1	Full Body Harness				
DPTHF2	Full Body Harness				
DPTHF3	Full Body Harness				





FallTech Test Report						
Test Report No.	PC-1898	Rpt. Date	7/24/2020	Rpt. Rev		Rev Date
Report Prepared For	For FallTech					
Initiated By	Dan Redden	Tact Specification(c)		ANSI Z359.11-2014 4.3.5, 4.3.3, 4.3.4, 4.3.7		7
Part No.	8143SM			Part No. Re	vision	А
Part Description	Ironworker Full Body Harness					
Test Request No.	PC-1898	PC-1898		Date Comp	lete	7/23/2020

Test Summary					
Test Specification	Tes	t Criteria	Test Result	Pass/Fail	
	Static Strength (Dorsal D-ring)	3600 Lbf ≥ 1 Minute	3636.1 Lbf	Pass	
ANGL 7350 44 2044	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass	
ANSI Z359.11-2014 4.3.5	Adjuster Slippage	Slippage ≤ 1"	0.43"	Pass	
4.5.5	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass	
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass	
	Static Strength (Dorsal D-ring)	3600 Lbf ≥ 1 Minute	3658.0 Lbf	Pass	
ANSI Z359.11-2014	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass	
4.3.5	Adjuster Slippage	Slippage ≤ 1"	0.34"	Pass	
4.3.3	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass	
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass	
	Static Strength (Dorsal D-ring)	3600 Lbf ≥ 1 Minute	3643.2 Lbf	Pass	
ANSI Z359.11-2014	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass	
4.3.5	Adjuster Slippage	Slippage ≤ 1"	0.40"	Pass	
4.3.3	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass	
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass	





FallTech Test Report						
Test Report No.	PC-1898	Rpt. Date	7/24/2020	Rpt. Rev		Rev Date
Report Prepared For	FallTech					
Initiated By	Dan Redden	Toot Chapification(a)		ANSI Z359.11-2014 4.3.5, 4.3.3, 4.3.4, 4.3.7		,
Part No.	8143SM	8143SM			vision	A
Part Description	Ironworker Full Body Harness					
Test Request No.	PC-1898			Date Comp	lete	7/23/2020

Test Summary (Continued)						
Test Specification	Test	Criteria	Test Result	Pass/Fail		
	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	4617.8 Lbf	Pass		
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass		
ANSI Z359.11-2014 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Remain Suspended for <u>></u> 5 Minutes	5 Minutes	Pass		
4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Angle at Rest ≤ 30°	1.6°	Pass		
	Dynamic Performance Dorsal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass		
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	9.9"	Pass		
	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	4657.6 Lbf	Pass		
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass		
ANSI Z359.11-2014 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Remain Suspended for <u>></u> 5 Minutes	5 Minutes	Pass		
4.5.5	Dynamic Performance Dorsal D-ring (Feet First)	Angle at Rest ≤ 30°	3.7°	Pass		
	Dynamic Performance Dorsal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass		
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	10.6"	Pass		
	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	3688.3 Lbf	Pass		
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass		
ANSI Z359.11-2014 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass		
4.5.5	Dynamic Performance Dorsal D-ring (Feet First)	Angle at Rest ≤ 30°	3.1°	Pass		
	Dynamic Performance Dorsal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass		
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	12.0"	Pass		





FallTech Test Report						
Test Report No.	PC-1898	Rpt. Date	7/24/2020	Rpt. Rev		Rev Date
Report Prepared For	FallTech	FallTech				
Initiated By	Dan Redden	Toot Chapification(a)		ANSI Z359.11-2014 4.3.5, 4.3.3, 4.3.4, 4.3.7		7
Part No.	8143SM			Part No. Re	vision	А
Part Description	Ironworker Full Body Harness					
Test Request No.	PC-1898			Date Comp	lete	7/23/2020

Test Summary (Continued)						
Test Specification	Test	Criteria	Test Result	Pass/Fail		
	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact Load ≥ 3,600 Lbf	1722.0 Lbf	*		
ANG 7250 44 2044	Dynamic Performance Dorsal D-ring (Head First)	Harness Shall Not Release Test Torso	Did Not Release	Pass		
ANSI Z359.11-2014 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Remain Suspended for <u>></u> 5 Minutes	5 Minutes	Pass		
	Dynamic Performance Dorsal D-ring (Head First)	Angle at Rest ≤ 30°	7.1°	Pass		
	Dynamic Performance Dorsal D-ring (Head First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass		
	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact Load ≥ 3,600 Lbf	1876.9 Lbf	*		
ANG 7050 44 0044	Dynamic Performance Dorsal D-ring (Head First)	Harness Shall Not Release Test Torso	Did Not Release	Pass		
ANSI Z359.11-2014 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Remain Suspended for <u>></u> 5 Minutes	5 Minutes	Pass		
	Dynamic Performance Dorsal D-ring (Head First)	Angle at Rest ≤ 30°	3.6°	Pass		
	Dynamic Performance Dorsal D-ring (Head First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass		
	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact Load ≥ 3,600 Lbf	1914.8 Lbf	*		
ANG 7050 44 0044	Dynamic Performance Dorsal D-ring (Head First)	Harness Shall Not Release Test Torso	Did Not Release	Pass		
ANSI Z359.11-2014 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Remain Suspended for \geq 5 Minutes	5 Minutes	Pass		
	Dynamic Performance Dorsal D-ring (Head First)	Angle at Rest ≤ 30°	3.5°	Pass		
	Dynamic Performance Dorsal D-ring (Head First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass		



FallTech Testing Laboratory

1306 S. Alameda Street, Compton, CA 90221-4803 Tel: (323) 752-0060 www.falltech.com

FallTech Test Report							
Test Report No.	PC-1898	Rpt. Date	7/24/2020	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)		ANSI Z359.11-2014 4.3.5, 4.3.3, 4.3.4, 4.3.7			
Part No.	8143SM			Part No. Re	vision	А	
Part Description	Ironworker Full Body Harr	ronworker Full Body Harness					
Test Request No.	PC-1898	•		Date Comp	lete	7/23/2020	

	Test Summary (Continued)						
Test Specification	Test Criteria		Test Result	Pass/Fail			
ANSI Z359.11-2014 4.3.7	Lanyard Parking Attachment Element	Disengagement Load ≤ 120 Lbf	Previously Tested and Passed under PC-1897	Pass			

Conclusion Based upon the samples provided to the Lab: FallTech P/N 8143SM Rev. A meets the requirements of ANSI Z359.11-2014

Test Exceptions

* Harness has been dynamically tested and subjected to forces of 5,000 Lbs. or more. Energy absorbing properties inherent to the harness prevented residual force readings equal to or greater than the 3,600 Lbs. required by the standard.

Report Signatories and Approval					
Lab Quality Manager	Jag Sponholz	Date	7/24/2020		
Witnessed by	Not Required	Date	N/A		