Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014



Alexander Andrew, Inc. 1306 S. Alameda St Compton, CA 90221

Declaration #	C12150	20	Dec	claration Date	12.29.15
Tested Item #	8259	6' Into	ernal Shock	Absorbing I	Lanyard
Additional Items	Conforming Und	er this Declaration:			
:	8259L 82	593 82593L	A8259		
Δlevander Δ	ndrew Inc. de	eclares that the p	roduct(s) liste	d ahove is in cor	oformity with
Alexander A		ents of the follo			=
		ANSI Z359	9.13-2013		
Cor	nformity Assess	ment Method in a	ccordance with	ANSI/ISEA 125-20	014
L	evel 1	Level 2	X	Level 3	
Level 1: Fall Outside the ISO/IEC Standard	Scope of	Level 2 : Fa Within the ISO/IEC Standa	Scope of	accr	ndent 3rd Party Lab edited to idard 17025:2005
Supporting Documentation	PC-0747				
Aut	horized Signati	ure	Dun	Jui	
lame Dusti	n Hawkins	Title ^V	P Business Develo	opment r	Date 1.25.16

Exova 3883 East Eagle Drive Anaheim California USA 92807 T: +1 (714) 630-3003 F: +1 (714) 630-4443 E: sales@exova.com W: www.exova.com

EXOVQ OCM

Testing. Advising. Assuring.

January 11, 2016

FallTech Testing Laboratory 1306 S. Alameda Street Compton, CA 90221

Attention: Jay Sponholz

Quality Manager

Subject: Attestation of Witnessing Testing

Exova OCM Job # 351807-1
FallTech P.O.: OPEN
Report No.: PC-0747
Base Part No. 8259

Description: Energy Absorbing Lanyard

Dear Mr. Sponholz:

The purpose of this attestation is to attest to the fact that a representative of Exova OCM was on site at FallTech's facilities to confirm suitability of the equipment used, calibration status of the equipment and to witness testing performed by FallTech employees. Details of this visit are included below:

- · Date of Testing:
 - December 9, 2015
- Exova OCM Test Witness:
 - Robert Fortner
- FallTech Test Operators:
 - Yesbet Sierra
- · Specification:
 - ANSI Z359.13-2013 Sections 4.5, 4.6, 4.13.1, 4.13.2, 4.13.3
- Equipment Calibration Interval
 - 1 year, except weights which are 5 years



Attached to this attestation is the test report generated by FallTech Testing Laboratory. Exova OCM test witness certifies the report accurately presents the testing performed on the samples identified.

Test Report #	Date	Base Part #	Description	Sample ID's	Results
				2927240	
				2927236	
				2927238	
				2927240	
				2927236	
				2927238	
				2927235	
PC-0747 12/29/2015	8259	Energy Absorbing Lanyard	2927232	Pass	
				2927241	
				2927231	
				2927234	
			2927233		
			2927243		
				2927239	
				2927245	

Test Witness Signature:	(Signed for and on behalf of Exova-OCM)	
Robert Fortner Technician Mechanical Laboratory	Robert Toutun	65 00 00 00 00 00 00 00 00 00 00 00 00 00

Approval Signature:	(Signed for and on behalf of Exova-OCM)	
Bruce K. Sauer Technical Director	Fank Com	OCA O56 Approxim

Technical Director	Sank Com	(5056 APPROX	
Approval Signature:	(Signed for and on behalf of Exova-OCM)	<u> </u>	

Thomas I (Tom) Davison		COUM
Thomas J. (Tom) Parsons Manager	the marson	APPROVE
Quality / Technical Services	5 00	OFFI OF THE OFFI OF THE OFFI OF THE OFFI OF THE OFFI OFFI OFFI OFFI OFFI OFFI OFFI OFF

This attestation shall not be reproduced except in full, without the written approval of Exova-OCM. The laboratory has witnessed the testing the material / items supplied by the client as sampled by the client. The testing is not within Exova OCM's L.A.B scope of testing and was not performed at Exova OCM.



FallTech Testing Laboratory Attestation Number: 351807-1 Revision Letter: Original Page 2 of 2



FallTech Testing Laboratory

1306 S. Alameda Street, Compton, CA 90221-4803 Tel: (323) 752-0060 www.falltech.com

FallTech Test Report							
Test Report Number	PC-0747	Date	12/29/2015	Rev		Rev Date	
Report Prepared For	FallTech	allTech					
Initiated By	Dan Redden	Pan Redden Test Specification ANSI Z359.13-2013 4.5, 4.6, 4.13.1, 4.13.2, 4.13.3					
Base Part #	8259	Descriptio	n	Energy Abs	orbing Lan	yard	
Proposed Part #	N/A	Built By Whom Production BOM No		No			
Test Request #	PC-0747	Date Received		12/10/2015	Date	Complete	12/10/2015
Test Operator	Yesbet Sierra	Test Opera	itor	Oscar Jaramillo			

	Material/Sample Identification					
Sample ID	Description					
2927240	Energy Absorbing Lanyard					
2927236	Energy Absorbing Lanyard					
2927238	Energy Absorbing Lanyard					
2927240	Energy Absorbing Lanyard					
2927236	Energy Absorbing Lanyard					
2927238	Energy Absorbing Lanyard					
2927235	Energy Absorbing Lanyard					
2927232	Energy Absorbing Lanyard					
2927241	Energy Absorbing Lanyard					
2927231	Energy Absorbing Lanyard					
2927234	Energy Absorbing Lanyard					
2927233	Energy Absorbing Lanyard					
2927243	Energy Absorbing Lanyard					
2927239	Energy Absorbing Lanyard					
2927245	Energy Absorbing Lanyard					

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to the joint ISO-ILAC-IAF Communique dated January 2009).

FallTech Testing Laboratory allows for a +/- 5% tolerance on dynamic performance and static strength test results.



FLT-08 Rev. F 08/03/2015



FallTech Testing Laboratory

1306 S. Alameda Street, Compton, CA 90221-4803 Tel: (323) 752-0060 www.falltech.com

FallTech Test Report							
Test Report Number	PC-0747	Date	12/29/2015	Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden Test Specification ANSI Z359.13-2013 4.5, 4.6, 4.13.1, 4.13.2, 4.13.3						
Base Part #	8259	59 Description Energy Absorbing Lanyard					
Proposed Part #	N/A	Built By Whom		Production		BOM	No
Test Request #	PC-0747	Date Rece	ived	12/10/2015	Date	Complete	12/10/2015

Test Summary						
Test Specification	Test	Criteria	Test Result	Pass/Fail		
ANSI Z359.13-2013	Arrest Distance	<u><</u> 48"	37.9"	Pass		
4.5	Max Arrest Force	<u><</u> 1800 Lbf	1314.3 Lbf	Pass		
4.5	Avg Arrest Force	<u>≤</u> 900 Lbf	771.1 Lbf	Pass		
ANCI 7250 12 2012	Arrest Distance	<u><</u> 48"	36.6"	Pass		
ANSI Z359.13-2013 4.5	Max Arrest Force	<u><</u> 1800 Lbf	1188.2 Lbf	Pass		
4.5	Avg Arrest Force	<u><</u> 900 Lbf	731.7 Lbf	Pass		
ANSI Z359.13-2013	Arrest Distance	<u><</u> 48"	37.3"	Pass		
4.5	Max Arrest Force	<u><</u> 1800 Lbf	922.5 Lbf	Pass		
4.5	Avg Arrest Force	<u><</u> 900 Lbf	758.9 Lbf	Pass		
ANSI Z359.13-2013	Static Strength	≥ 5000 Lbf	5030.2 Lbf	Pass		
4.6	Hold	≥ 1 Minute	1 Minute	Pass		
ANSI Z359.13-2013	Static Strength	≥ 5000 Lbf	5043.3 Lbf	Pass		
4.6	Hold	≥ 1 Minute	1 Minute	Pass		
ANSI Z359.13-2013	Static Strength	≥ 5000 Lbf	5021.0 Lbf	Pass		
4.6	Hold	≥ 1 Minute	1 Minute	Pass		
ANCI 7250 42 2042	Arrest Distance	<u><</u> 48"	37.9"	Pass		
ANSI Z359.13-2013 4.13.1	Max Arrest Force	≤ 1800 Lbf	1099.6 Lbf	Pass		
4.13.1	Avg Arrest Force	≤ 1125 Lbf	811.9 Lbf	Pass		
ANSI Z359.13-2013	Arrest Distance	<u><</u> 48"	39.2"	Pass		
4.13.1	Max Arrest Force	<u><</u> 1800 Lbf	1032.1 Lbf	Pass		
4.13.1	Avg Arrest Force	<u><</u> 1125 Lbf	780.1 Lbf	Pass		
ANCI 7250 42 2042	Arrest Distance	<u><</u> 48"	38.7"	Pass		
ANSI Z359.13-2013 4.13.1	Max Arrest Force	<u><</u> 1800 Lbf	1169.9 Lbf	Pass		
4.13.1	Avg Arrest Force	≤ 1125 Lbf	823.1 Lbf	Pass		

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to the joint ISO-ILAC-IAF Communique dated January 2009).

FallTech Testing Laboratory allows for a +/- 5% tolerance on dynamic performance and static strength test results.



FLT-08 Rev. F 08/03/2015



FallTech Testing Laboratory

1306 S. Alameda Street, Compton, CA 90221-4803 Tel: (323) 752-0060 www.falltech.com

	F	allTech Test R	eport		
Test Report Number	PC-0747	Date 12/29/2015	Rev	Rev Date	
Report Prepared For	FallTech				
Initiated By	Dan Redden	Test Specification	ANSI Z359.13-2013 4.5, 4.6, 4.13.1, 4.13.2, 4.13.3		
Base Part #	8259	Description	Energy Absorbi	ing Lanyard	
Proposed Part #	N/A	Built By Whom	Production	BOM No	
Test Request #	PC-0747	Date Received	12/10/2015	Date Complete 12/10/2015	
41/2/ 7050 40 0040	Arrest Distance	≤ 48"	27.7"	Pass	
ANSI Z359.13-2013 4.13.2	Max Arrest Force	≤ 1800 Lbf	1264.6 Lb	of Pass	
4.15.2	Avg Arrest Force	≤ 1125 Lbf	900.6 Lbf	f Pass	
ANG 7050 40 0040	Arrest Distance	≤ 48"	27.7"	Pass	
ANSI Z359.13-2013 4.13.2	Max Arrest Force	≤ 1800 Lbf	1272.0 Lb	of Pass	
4.13.2	Avg Arrest Force	≤ 1125 Lbf	922.2 Lbf	f Pass	
ANG 7250 42 2042	Arrest Distance	≤ 48"	26.8"	Pass	
ANSI Z359.13-2013 4.13.2	Max Arrest Force	≤ 1800 Lbf	1409.1 Lb	of Pass	
4.13.2	Avg Arrest Force	≤ 1125 Lbf	919.7 Lbf	f Pass	
ANG 7050 40 0040	Arrest Distance	≤ 48"	42.7"	Pass	
ANSI Z359.13-2013 4.13.3	Max Arrest Force	≤ 1800 Lbf	944.8 Lb	f Pass	
4.15.5	Avg Arrest Force	≤ 1125 Lbf	683.2 Lbt	f Pass	
ANGI 7250 42 2042	Arrest Distance	≤ 48"	41.5"	Pass	
ANSI Z359.13-2013 4.13.3	Max Arrest Force	≤ 1800 Lbf	899.2 Lb	f Pass	
4.13.3	Avg Arrest Force	≤ 1125 Lbf	679.3 Lb	f Pass	
ANGL 7250 42 2042	Arrest Distance	≤ 48"	43.7"	Pass	
ANSI Z359.13-2013 4.13.3	Max Arrest Force	≤ 1800 Lbf	931.4 Lb	f Pass	
4.12.2	Avg Arrest Force	≤ 1125 Lbf	689.4 Lb	f Pass	

Conclusion

FallTech P/N 8259 meets the requirements of ANSI Z359.13-2013.

Report Signatories and Approval						
Lab Quality Manager	Date	12/29/2015				
Witnessed by	Robert Fortun	Date	412/16			

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to the joint ISO-ILAC-IAF Communique dated January 2009).

FallTech Testing Laboratory allows for a +/- 5% tolerance on dynamic performance and static strength test results.