

iN2-2P ProFusion Injection Device



Specifications

- 10.5"W x 4.5"D x 12.75"H includes top and bottom mounting bracket
- One gas inlet, dual gas control for keg and injector pressures
- One product from keg inlet, two product outlets
- Built in stainless steel particulate filter, 50 micron, washable and reusable
- Allow 4" clearance recommended for easy access to regulators and particulate filter




Project:

<u>Scan for more info!</u> Owners manual Install guide

N₂ and CO₂ Beverages on Tap

- Easily add a ProFused beverage to your draft system.
- The iN2-2P injector is designed for use in a back bar, direct draw cooler or walk-in box when paired with our iN2 draft tower.
- The ProFusion system uses one cold keg of cold brew coffee, tea or your craft beverage of choice and dispenses two different style beverages from a single keg
- Nitrogenated or lightly carbonated, and Still Beverage on Tap.
- Simple set-up configuration: One keg connection, two outlets. One gas connection, feeds both the system and keg (each with their own pressure control).
- High visibility and easy accessible particulate filter
- Compact, thin design that can easily fit in coolers and not take up excessive space.
- Weight: 6.25 lbs
- Stainless steel enclosure
- John Guest® swivel fittings and barb to stem adaptors
- All other components supplied separately per customers use and set-up
- Must be located in a refrigerated space within five feet of dispensing tower
- Liquid and gas inlet/outlet ports are on one side of the iN2-2P injector



Accessories:

CR-PMT-5G
5 gallon premix tank



Gas Ball Lock
Disconnects for premix tank



 CR-N2 Stout faucet for N2 beverage



CR-742N
Primary N2 tank regulator
CR-3741
Primary O2 tank regulator



 CR-CUSTAP
Custom tap handles. Contact factory for options and details.



Crysalli Beverage Systems a division of WPD 1739 Sabre Street, Hayward, CA 94545

CR-PMT-2.5G2.5 gallon premix tank



Liquid Ball Lock
Disconnects for premix tank




CR-G26SS
304 stainless steel nitro faucet



CR-153-5SS
304 stainless steel shank
used with CR-G26SS nitro faucet



 CR-CUSTOWER
Custom draft tower. Contact factory for options and details.



 1-2Coldbrew
Cleaning and sanitizing kit for cold brew systems



Keg Coupler
D Style stainless steel



 CR-SSX0101 HEX faucets, for premix beverage



CR-X5SHNK 5" wall shank





CR07272020

www.crysalli.com