
35.00 [889.00mm] **REAR VIEW** B 1.50 [38.10mm] 8.00 [203.20mm] [508,00mm] MOUNTING HOLES FOR 3/8" DIAMETER GOAL AND BOARD MOUNTING HARDWARE. 12 GA STEEL STAMPED SHELL WITH 12 GA. FORMED MOUNTING AND 20.00 42.00 1066.80mm] STIFFENING CHANNELS WELDED TO REVERSE SIDE. BOARD IS POWDER COATED GLOSS WHITE. 5.00 [127.00mm] FRONT VIEW 72.00 [1828.80mm] [127.00mm]





Gared Holdings, LLC 9200 E. 146th St. Noblesville, IN 46060 THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

42" X 72" RECTANGULAR STEEL BACKBOARD

12 X 12 1(201) (1002) (10012) (1000)									
DRAWN CONNERLEY			DATE	11/16/06	MATERIAL AS NOTED				
APPROVED JJC			DATE	11/16/06	FINISH AS NOTED				
FILE LOC	Q:\Final	Release	e\Spec	ifications		DWG. NO.	1272		
SIZE	SCALE	SHT. I	NO.	PART NO.				F	REV
Α	NOTED	1 OF	1		1272				Α





MODEL 1272

72" X 42" RECTANGULAR STEEL BACKBOARD

The 1272 backboard shall be formed from a single piece of heavy gauge steel and reinforced with a heavy gauge vertical center channel and heavy gauge horizontal channels. All reinforcing sections shall be welded to the shell to make a single vibration free unit. Manufacturer of backboard shall have over ten years experience producing such item.

Key-slots in the horizontal channels shall be spaced at 20" vertical and 35" horizontal. Backboard shall be phosphate pre-treated and shall have a durable white powder coat finish to protect against weathering. Goal mounting holes shall be on 5" horizontal and 5" vertical centers.

ACCESSORIES

GOALS

Compatible goals are models 726, 5500, 7550, 7555, 140, 240, 39WO, 3942, and 4039. See goal section in specification manual.