



MODEL	FINISH	KEY REQUIRED
6430	POLISHED BRASS	YES
6431	CHROME	YES

REVISION		
REV.	DATE	BY
A	09-23-15	WDC
B	06-24-16	WDC




Gared Holdings, LLC
9200 E. 146th St. Noblesville, IN 46060

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

STANDARD SIZE LOW PROFILE FLOOR COVER

DRAWN	CONNERLEY	DATE	08/18/08	MATERIAL	N/A
APPROVED	CONNERLEY	DATE	08/18/08	FINISH	N/A
FILE LOC. Q:\Final Release\Specifications				DWG. NO.	6430
SIZE	SCALE	SHT. NO.	PART NO.	6430	
A	NOTED	1 OF 1			
				REV	A



MODEL 6430 / 6431

**LOW PROFILE VOLLEYBALL FLOOR COVER
STANDARD SIZE**

Floor cover shall be brass plated steel for model 6430 and chrome plated steel for model 6431. Cover plate shall have a molded plastic recessed mounting flange, cork gasket, and 6 3/16" diameter cover. Molded plastic recessed mounting flange shall be 6 7/16" in diameter and have 3 holes in the ring (for screwing into the floor) that shall be completely concealed under the cover when in the closed position, allowing for a completely flat surface. In a "floating" wood floor, the floor plate is connected to the floor only, allowing it to move with the expansion and contraction of the floor. Cover shall be 6-3/16" in diameter by 1/4" thick. Diameter of opening shall be 5 3/16 ".

6430 - Polished Brass finish with key

6431 – Chrome finish with key

Subject to design change and current manufacturing practices.
Revised June 24,2016 ©2008 Gared Holdings, LLC