



REAR VIEW

FRONT VIEW

NOTE:
 BACKBOARD THICKNESS - 2 1/8".
 MATERIAL - 1/2" THICK TEMPERED GLASS WITH ALUMINUM FRAME.
 FINISH - GRAY POWDERCOAT ON BRACKETS AND PLATES.

REVISION		
REV.	DATE	BY
A	12/01/03	JJC
B	06/06/08	RWP




Gared Holdings, LLC
 9200 E. 146th St. Noblesville, IN 46060

THIS DOCUMENT CONTAINS TRADE SECRET AND OTHER MATERIALS WHICH ARE PROTECTED BY CONFIDENTIALITY NOTICE AND AGREEMENT AND BY COPYRIGHT. ANY USE OR COPYING OF THIS DOCUMENT EXCEPT AS AUTHORIZED BY GARED HOLDINGS, LLC IS STRICTLY PROHIBITED.

42" ALUMINUM FRAME GLASS BACKBOARD

DRAWN	CONNERLEY	DATE	05/02/03	MATERIAL	AS NOTED
APPROVED	JJC	DATE	05/02/03	FINISH	AS NOTED
FILE LOC. Q:\Final Release\Specifications				DWG. NO.	AFRG42
SIZE	SCALE	SHT. NO.	PART NO.	REV	
A	NOTED	1 OF 1	AFRG42	B	



MODEL AFRG42

ALUMINUM FRAME 72" X 42" RECTANGULAR GLASS BACKBOARD

The AFRG42 backboard shall be fabricated with an aluminum frame constructed of 0.200" thick extruded "F" channel with steel corner brackets. All steel components shall be powder coated with a durable gray finish. Aluminum-capped frame will not be acceptable. Manufacturer of backboard shall have over ten years experience. Backboard shall meet NCAA and high school requirements.

Glass shall be 1/2" in thickness and fully tempered with white border and target lines permanently fused onto the surface. 12mm glass will not be considered equal to 1/2" glass, with a nominal thickness range of .485" to .515", and will not be used as a substitute for full 1/2" glass. Vinyl shock absorbing material insulates the glass from the frame. Goal mounting holes shall be on standard 5" horizontal and 4" vertical centers. Acrylic cushioning pad shall be used between steel mounting plate and glass to protect against possible breakage.

ACCESSORIES

GOALS

Compatible goals are models 1000, 2000+, 2500, 2500I, 3000, 20123T-B (Snap B), and 5500. See goal section in specification manual.

Subject to design change and current manufacturing practices.
Revised April 4, 2008 ©2008 Gared Holdings, LLC